

RUST-OLEUM®
— INDUSTRIAL —



6020 QUICK DRYING PRIMER



Quick drying moisture- controlling primer

- Quick drying
- Good hiding power and filling performance
- Good edge coverage

KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

6020 QUICK DRYING PRIMER

DESCRIPTION

Quick drying, good filling, moisture-controlling primer based on an alkyd resin. Suitable for woodwork and pre-treated metal. Available in white, grey and black. For exterior use.

RECOMMENDED USE

Rust-Oleum Rapid Primer is a quick-drying, high-build, moisture regulating primer based on alkyd resin. Dry after one hour. Repaintable after five hours. To be used in combination with Rust-Oleum lacquers for maximum durability. For outdoor use.

RECOMMENDED SYSTEM

Suitable as a primer on wood, existing coating of alkyd layers, and as an intermediate coating on pre-treated metal. Rust-Oleum Rapid Primer is suitable for a continuous work situation or for maintenance work where a finishing layer (topcoat) must be applied the same day. Rust-Oleum Rapid Primer can remain unaffected for several months without any problems and can be applied to wood with a maximum moisture level of 20%.

TECHNICAL DATA

Density (g/cm³): Ca 1.65 g/ml
Solids content in volume: 65%

DRY TIMES BY 20° C/RH 50%

Touch dry: After 1 hour
Dry to handle: After approx. 2 hours
Dry to recoat: After 5 hours

RECOMMENDED WET FILM THICKNESS

62 µm

RECOMMENDED DRY FILM THICKNESS

40 µm

THEORETICAL CONSUMPTION

Approx. 16 m²/litres per coat

PRACTICAL CONSUMPTION

The actual usage is dependent on the nature and structure of the surface and the processing method.

SURFACE PREPARATION

The surface must be sound, clean, dry, and free of dust and grease. With wood frames, round off sharp edges so that you can apply a good coating.

Treated/untreated wood

- Clean all the wood using Universol.
- Sand away discoloured wood down to the healthy wood and prime with Rust-Oleum Multiprimer.
- Carry out repairs as needed, sand, and remove all dust.
- Prime untreated wood with Rust-Oleum Rapid Primer.
- Once dry, sand lightly, and remove all dust.
- Finish with a lacquer, such as Rust-Oleum Combicolor or Mathys Fassilux.

Existing old layers

- Remove old loose layers.
- Clean all the wood using Universol.
- Sand away discoloured wood down to the healthy wood and prime with Rust-Oleum Rapid Primer.
- Carry out repairs as needed and prime with Rust-Oleum Rapid Primer.
- Once dry, sand, and remove all dust.
- Prime stripped parts with Rust-Oleum Rapid Primer.
- Once dry, sand lightly, and remove all dust.
- Finish with a lacquer, such as Rust-Oleum Combicolor or Mathys Fassilux.

Existing intact paint layers

- Clean the intact layers using Universol.
- Thoroughly sand the surface.
- Retouch with Rust-Oleum Rapid Primer.
- Once dry, sand lightly and remove all dust.
- Finish with a lacquer, such as Rust-Oleum Combicolor or Mathys Fassilux.

The above systems serve as a general description for most common surfaces. For special applications and/or extensive advice, feel free to contact Rust-Oleum Europe.

DIRECTIONS FOR USE

Stir thoroughly before use. Use a suitable brush or roller to apply one or more layers. Always work wet-on-wet to prevent brush marks. Do not retouch when drying.

APPLICATION CONDITIONS

Do not apply paint at temperatures below +8°C. Apply paint only when the surface temperature is at least 3°C above its dew point. Do not apply outdoors when rain or frost threatens, nor in bright sunlight.

APPLICATION & THINNING: BRUSH

Ready for use. Use a long-haired natural brush.

APPLICATION & THINNING: ROLLER

Ready for use. Use a nylon roller that is suitable for applying synthetic paints.

CLEANING OF EQUIPMENT / SPILLS

White spirit or brush cleaner

Date issued: 20/03/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T: +31 (0) 165 593 636
F: +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T: +44 (0)1914 113 146
F: +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T: +33(0) 130 40 00 44
F: +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T: +32 (0) 13 460 200
F: +32 (0) 13 460 201
info@rust-oleum.eu

6020 QUICK DRYING PRIMER

REMARKS

The product can be used down to a temperature of 0°C. Drying will be slower at lower temperatures. Variations in layer thickness, temperature, humidity, etc. affect the drying time.

General: the values listed in this technical information leaflet are set in accordance with DIN EN 13300.

Always wear the necessary personal protective equipment when working with this product. Always ensure there is adequate ventilation when working with the paint.

Remnants: Take this product and the packaging to a collection point for hazardous or special waste.

SAFETY DATA

VOC readymix: 269g/l
Remarks regarding safety: Refer to the associated product safety leaflet and the information on the packaging.

SHELF LIFE

Minimum of 12 months from the date of production when kept in unopened cans, original packaging, stored in a dry, well-ventilated area, and not placed in direct sunlight, at temperatures between 5°C and 25°C.

Date issued: 20/03/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T: +31 (0) 165 593 636
F: +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T: +44 (0)1914 113 146
F: +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T: +33(0) 130 40 00 44
F: +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T: +32 (0) 13 460 200
F: +32 (0) 13 460 201
info@rust-oleum.eu