

RUST-OLEUM®
INDUSTRIAL



6210 PROJECT MAT INTERIOR

Matt, solvent-free wall paint



KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

6210 PROJECT MAT INTERIOR

DESCRIPTION

Matt, solvent-free wall paint for painting walls and ceilings. Convenient for application in large-scale construction and renovation projects. For application in dry areas. For interior use.

RECOMMENDED USE

Matt, solvent-free wall paint based on emulsion and is particularly intended to paint indoor walls and ceilings of large newly-constructed or renovated projects. Universally usable in dry spaces.

RECOMMENDED SYSTEM

As a wall paint for renovated and new constructions on mineral surfaces. Suitable surfaces include: existing wall paint layers, cement and plaster, concrete, brick, plasterboard, etc. It is also suitable for painting fibreglass.

TECHNICAL DATA

Density (g/cm³): Ongeveer 1.55 g/ml
Gloss level at 85°: Matt: 9%
Solids content in volume: 40%

DRY TIMES BY 20° C/RH 50%

Dry to handle: 2 hours
Dry to recoat: 4 to 6 hours

RECOMMENDED WET FILM THICKNESS

142 µm

RECOMMENDED DRY FILM THICKNESS

57 µm

THEORETICAL CONSUMPTION

Approx. 7m²/litres per coat

PRACTICAL CONSUMPTION

Actual usage is dependent on the nature and structure of the surface and the processing method.

SURFACE PREPARATION

The surface must be load-bearing, completely cured, clean, dry, and free of dust and grease. Repair flakes and cracks. Remove and/or repair loose and unstable layers.

New, untreated surfaces

- Pre-treat all highly porous surfaces with Mathys Pegafix.
- Thoroughly clean powdery surfaces. Once dry, pretreat with Mathys Pegafix.
- Once dry, apply a finishing layer.

Existing intact wall paint layers

- Clean using Universol.
- If necessary, apply an intermediate layer of Mathys Paracem Deco Primer.
- Once dry, apply a finishing layer.

Existing, non-load-bearing wall paints

- Remove loose parts.
- Thoroughly wash powdery layers and allow to dry.
- Carry out repairs as needed.
- Pre-treat with Mathys Pegafix.
- Once dry, apply a finishing layer.

Contaminants caused by nicotine, moisture, rust or soot

- Thoroughly clean using Universol.
- Treat surface contaminants with Mathys Pegamat Aqua Isole.
- Once dry, apply a finishing layer (overcoat).

The above systems serve as a general description for most common surfaces. For special applications and/or extensive advice, feel free to contact Rust-Oleum Europe.

DIRECTIONS FOR USE

Stir thoroughly before use. If necessary, thin first layer with a maximum of 10% water. Apply using a suitable brush, roller or spray-gun. Always work wet-on-wet to prevent brush marks. Apply all strokes in the same direction. Do not touch up while drying.

APPLICATION CONDITIONS

Do not apply paint at temperatures below +8°C. Only apply paint when the surface temperature is at least 3°C above its dew point.

APPLICATION & THINNING: AIRLESS SPRAY

Airmix
Nozzle: 0.017-0.019" / Pressure: approx. 150-180 bar
Air pressure: approx. 2 bar

Airless
Nozzle: 0.017-0.019" / Pressure: approx. 220-250 bars

The settings listed for spraying this product are a guideline. The painter will need to determine the actual settings depending on the circumstances.

CLEANING OF EQUIPMENT / SPILLS

Clean with water and soap.

Date issued: 20/03/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T: +31 (0) 165 593 636
F: +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T: +44 (0)1914 113 146
F: +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T: +33(0) 130 40 00 44
F: +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T: +32 (0) 13 460 200
F: +32 (0) 13 460 201
info@rust-oleum.eu

6210 PROJECT MAT INTERIOR

REMARKS

General: the values listed in this technical information leaflet are set in accordance with DIN EN 13300.

Always wear the necessary personal protective equipment when working with this product. Do not inhale this product's vapour or spray mist. Always ensure there is adequate ventilation when working with the paint.

Remnants: Take this product and the packaging to a collection point for hazardous or special waste.

SAFETY DATA

VOC readymix: 5 g/l
Remarks regarding safety: Refer to the associated product safety leaflet and the information on the packaging.

SHELF LIFE

Minimum of twelve months from the date of production when kept in unopened cans, original packaging, stored in a dry, well-ventilated area, and not placed in direct sunlight, at temperatures between 5°C and 25°C.

Date issued: 20/03/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T: +31 (0) 165 593 636
F: +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T: +44 (0)1914 113 146
F: +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T: +33(0) 130 40 00 44
F: +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T: +32 (0) 13 460 200
F: +32 (0) 13 460 201
info@rust-oleum.eu