



## ALUREX FORTE

# For cleaning severely dirty aluminium and steel

- Removes heavy grime from aluminium and steel
- Does not contain abrasives
- Can be rinsed off with water
- Dilute maximally to a ratio of 1: 20

# ALUREX FORTE

## DESCRIPTION

A highly-concentrated aluminium cleaner/pre-treatment agent based on organic and inorganic acids for treating and cleaning corroded aluminium and stainless steel.

## RECOMMENDED USE

Alurex Forte is suitable for cleaning/pre-treating heavily corroded aluminium and stainless steel.

## PRACTICAL CONSUMPTION

Consumption is heavily dependent on the degree of fouling and corrosion.

## DIRECTIONS FOR USE

- Dilute Alurex Forte with water maximally to a ratio of 1: 20 depending on the degree of fouling and the extent of corrosion.
- Work from the bottom to the top to avoid runs and streaks.
- Apply the product with a cloth, sponge, wide brush, or hand brush and allow to soak in for a maximum of 5 minutes
- Prevent spatters and drips.
- Do not allow the product to dry out
- Rinse off thoroughly with water.
- A car-washing brush or white pad may be used as an aid.

## APPLICATION CONDITIONS

Minimum ambient temperature : 5 °C  
Maximum relative humidity : 100%  
Minimum surface temperature: 5 °C  
Maximum surface temperature: 25 °C

## CLEANING OF EQUIPMENT / SPILLS

Rinse with clean water immediately after use.

## REMARKS

Dispose of the product and empty packaging as chemical waste in accordance with the local regulations and legal requirements.

### Hazard

- Fatal when swallowed and in contact with the skin
- Poisonous when inhaled.
- Causes serious burns and eye injuries

### Prevention

- Thoroughly wash your hands after working with this product.
- Only use outdoors or in a well-ventilated space.
- Do not eat, drink, or smoke when using this product.
- Wear protective gloves and face protection.
- Wear an apron or overalls when there is a chance of spatters.
- Wear goggles, face protection, or other full-face protection when there is a chance of direct exposure to aerosols or spatters.

### Reaction

#### AFTER INHALING:

- Bring the person out into fresh air and ensure that can breathe easily.
- Immediately consult a doctor.

#### AFTER SWALLOWING:

- Rinse the mouth.
- Do not induce vomiting.

#### CONTACT WITH THE SKIN (or hair):

- Immediately remove contaminated clothing.
- Rinse off the skin with water or take a shower.

#### CONTACT WITH THE EYES:

- Carefully rinse with water for several minutes.
- If possible, remove contact lenses.
- Continue to rinse.

### Storage

- In a well-ventilated location.
- Store in properly closed packaging.
- Keep locked up.
- Dispose of the content and container in accordance with local, regional, national, and international regulations.

## SHELF LIFE

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

Date issued: 05/02/2025

**Available colours & pack sizes:** Please refer to the respective product page on [www.rust-oleum.eu](http://www.rust-oleum.eu) for an overview of actual available colours and pack sizes.

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from [www.rust-oleum.eu](http://www.rust-oleum.eu) or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)