



## ALUREX SPECIAL PUMP SPRAY

# Removes surface rust from stainless steel & aluminium

- Removes surface rust and light dirt
- Contains no abrasives, does not damage surface
- Does not scratch glass or rubber
- Can be rinsed off with water
- Also suitable for stainless-steel, non-ferrous metals, and glass

# ALUREX SPECIAL PUMP SPRAY

## DESCRIPTION

Also removes light corrosion (surface rust), road and city grime, exhaust gas deposits, and industrial pollution.

Suitable for stainless steel, bare and anodised aluminium, painted metal, and glass.

## RECOMMENDED USE

Alurex Special Ready-to-Use is suitable for removing light corrosion, road and city grime, exhaust gas deposits, surface rust, industrial pollution, and so on, from painted metal, anodised aluminium, non-ferrous metals, glass, and stainless steel.

## PRACTICAL CONSUMPTION

Consumption is heavily dependent on the degree of dirt and corrosion.

## DIRECTIONS FOR USE

Do not dilute Alurex Special Ready-to-Use.

Work from the bottom to the top to avoid runs and stripes.

Apply the product using a spray bottle and allow to soak in for at least 5 minutes.

If necessary, use a car brush, sponge, or white pad as an aid.

Also available in as a concentrate for use in a refill spray bottle. Dilute to the mixture ratio of 150 ml Alurex Special Concentraat to 350 ml clean water. After use, rinse thoroughly with water until a neutral surface is obtained.

*First, try out a test surface.*

## APPLICATION CONDITIONS

Minimum ambient temperature : 5 °C

Maximum relative humidity : 100%

Minimum surface temperature : 5 °C

Maximum surface temperature: 25 °C

## CLEANING OF EQUIPMENT / SPILLS

Rinse with clean water immediately after use.

## PH

1

## SHELF LIFE

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

Date issued: 05/02/2025

**Available colours & pack sizes:** Please refer to the respective product page on [www.rust-oleum.eu](http://www.rust-oleum.eu) for an overview of actual available colours and pack sizes.

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from [www.rust-oleum.eu](http://www.rust-oleum.eu) or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)