

RUST-OLEUM®
INDUSTRIAL



BIOSAN® AQUA

Water-based hygienic wall paint in any colour

- Decorative hygienic paint in gloss, satin or mat in almost any colour
- Good flow, filling and hiding power
- For use on masonry, plaster, wood or concrete
- Ideal for schools, dressing rooms, kitchens etc.

KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

BIOSAN® AQUA

BESKRIVELSE

Water-based single pack hygienic topcoat for walls and ceilings where hygiene control is essential, tintable in many colours and different gloss levels.

ANBEFALET BRUG

For the interior and exterior coating of walls and ceilings in low wear areas, where hygiene is important. Rated Class 0 to the UK Building Regulations (BS476 Parts 6&7).

TEKNISK DATA

Tæthed:	1,2 - 1,4
Glansgrad:	Blank, Mat, Satin
Faststofindhold i vægt:	50-65 %
Tørstofindhold i volumen:	35-50 %

TØRRETIDER VED 20°C/50% RELATIV LUFTFUGTIGHED

Berøringstør:	45 minutes
Håndteringstør:	1 hour
Fuldt hærdet:	2 days

PRAKTISK FORBRUG

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

FORBEHANDLING AF OVERFLADEN

Painted substrates: apply directly on old sound paints, glossy paints will be roughed up slightly.

Untreated substrates: On woodwork, apply a coat of Fassiprim Aqua.

On masonry, plaster, and concrete: apply a coat of Pegalink first. Good adhering and slightly powdery surfaces have to be impregnated first with Pegafix after high pressure cleaning.

For stain, graffiti blocking and/or very fast recoating on all substrates, use Zinsser primers Bulls Eye 123 or 123 Plus.

BRUGSANVISNING

To ensure homogeneity, coating materials should be thoroughly stirred prior to use.

ANVENDELSESBETINGELSER

> 10°C; < 80% H.R.

PÅFØRING OG FORTYNDING: PENSEL

Apply with flat brush, do not dilute.

PÅFØRING OG FORTYNDING: RULLE

Apply with dispersion roller. Do not dilute.

PÅFØRING OG FORTYNDING: LUFTLØS SPRØJTE

Nozzle: 018 / Pressure: 180 bars. If necessary, dilute with some water.

PÅFØRING OG FORTYNDING: LUFTATOMISERET SPRØJTE

Dilute with maximum 5% volume water.

RENGØRING AF UDS TYR/SPILD

Water.

BEMÆRKNINGER

Do not apply in full sun or too hot conditions, to avoid that the product dries too fast and consequently to avoid a decreased flow. The use of Biosan products does not exclude the necessity to clean and disinfect on a normal and regular basis.

SIKKERHEDSDATA

VOC-niveau:	max. 110 g/l
VOC-færdigblanding:	max. 110 g/l
VOC-kategori:	A/i
VOC-grænse:	140 g/l
Bemærkninger om sikkerhed:	Consult Safety Data Sheet and Safety Information printed on the can.

HOLDBARHED

Minimum of 2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Udstedelsesdato: 14/02/2023

Tilgængelige farver og pakningsstørrelser: Der henvises til den respektive produktside på www.rust-oleum.eu for en oversigt over aktuelle tilgængelige farver og pakningsstørrelser.

Ansvarsfraskrivelse: Oplysningerne heri er efter vores bedste overbevisning korrekte, og er afgivet i god tro, men uden garanti. Brugeren vil blive anset for at selvstændigt at have bekræftet egnetheden af vores produkter til hans/hendes egen særlige formål. Rust-Oleum Europa kan under ingen omstændigheder holdes ansvarlig for følgeskader eller hændelige skader. Produkterne skal opbevares, håndteres og anvendes under forhold, der er i overensstemmelse med Rust-Oleum Europes anbefalinger beskrevet i den nyeste udgave af databladet. Det er brugernes ansvar at sikre, at de har den opdaterede udgave. De nyeste udgaver af datablade kan downloades gratis fra www.rust-oleum.eu eller tilsendes på anmodning til vores kundeservice. Rust-Oleum Europe forbeholder sig ret til at ændre egenskaberne for sine produkter uden forudgående varsel.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu