

**PROCHEMKO**



## COATEX SPECIAL IMPREGNATE

### Impregnator for Coatex Special system

- Excellent adhesion to a variety of surfaces
- Can be painted over quickly
- Colourless
- Does not yellow or chalk
- For absorbent surfaces

# COATEX SPECIAL IMPREGNATE

## DESCRIPTION

Two-component, solvent-based, highly penetrative, polyurethane impregnation agent for cement-based surfaces for the Coatex Special system.

## RECOMMENDED USE

Coatex Special Impregnate is an impregnating agent with a high depth of penetration in cement-based surfaces, masonry, concrete, and similar.

## TECHNICAL DATA

Density (g/cm<sup>3</sup>): 1,0 kg/l  
Gloss Level: Gloss  
Solids content in volume: 53%

## PRACTICAL CONSUMPTION

The actual consumption is dependent on the surface's absorptive capacity and the application method.

## DIRECTIONS FOR USE

Vigorously mix A and B components in the correct proportion until a homogeneous mixture is achieved. Do not dilute. Apply Coatex Special Impregnate using a brush, spray gun, or short-haired roller.

## APPLICATION CONDITIONS

Minimum ambient temperature: 5 °C.  
Maximum relative humidity: 80%  
Minimum surface temperature: 5 °C  
Maximum surface temperature: 35 °C

## CLEANING OF EQUIPMENT / SPILLS

Rinse with Coatex Special Thinner immediately after use.

## REMARKS

Remnants of this product and empty packaging should be treated as chemical waste and may not be disposed of together with commercial or household waste.

## SAFETY DATA

VOC level: 499 g/l  
VOC readymix: 499 g/l  
VOC category: A/j  
VOC limit: 500 g/l  
Remarks regarding safety: Consult the associated product safety leaflet and the information listed on the packaging.

## SHELF LIFE

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

Date issued: 05/02/2025

**Available colours & pack sizes:** Please refer to the respective product page on [www.rust-oleum.eu](http://www.rust-oleum.eu) for an overview of actual available colours and pack sizes.

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from [www.rust-oleum.eu](http://www.rust-oleum.eu) or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)