



## COATEX SPECIAAL NV

# Anti-graffiti coating in matt or gloss

- Very durable, scratch resistant, and chemically resistant
- Flexible and shock-resistant
- Does not yellow, UV resistant
- Available in matt and gloss, colourless, and with colour
- Colourless coating does not change the appearance of the surface



# COATEX SPECIAAL NV

## DESCRIPTION

Polyurethane two-component scratch-resistant anti-graffiti coating with good chemical and mechanical resistance and colour fastness.

## RECOMMENDED USE

Coatex Special NV is a durable anti-graffiti system for objects that must comply with the strictest requirements in terms of chemical and mechanical resistance.

### REMOVING GRAFFITI

- Apply Rodex to the surface to be cleaned.
- Apply Topper on the surface to be cleaned.
- Spray off with cold water (at maximally 35 bar)
- Treat the surface afterwards with Rodex diluted with water (1: 10)

## TECHNICAL DATA

Density (g/cm<sup>3</sup>): 1,07 kg/l (transparant) - 1,36 kg/l (kleur)  
Gloss Level: Gloss,Matt  
Solids content in volume: 56% (transparant) - 57% (kleur)

## PRACTICAL CONSUMPTION

Depends on many factors, such as porosity, roughness of the surface, and material loss when applying the paint.

## DIRECTIONS FOR USE

Vigorously mix A and B components in the correct proportion until a homogeneous mixture is achieved.

Dilute with Coatex Speciaal Thinner maximally 10%.

Apply Coatex Speciaal NV on a surface treated with Rust-Oleum 5401.

Apply the product using a brush, spray gun, or short-haired roller.

## APPLICATION CONDITIONS

Minimum ambient temperature : 10 °C

Maximum relative humidity : 80%

Minimum surface temperature : 10 °C

Maximum surface temperature: 35 °C

## CLEANING OF EQUIPMENT / SPILLS

Coatex Special Thinner.

## REMARKS

Dispose of remnants of the product and empty packaging as chemical waste in accordance with the local regulations and legal requirements.

## SAFETY DATA

VOC level: 468 g/l  
VOC ready mix: 468 g/l  
VOC category: A/j  
VOC limit: 500 g/l  
Remarks regarding safety: Consult the associated product safety leaflet and the information listed on the packaging.

## SHELF LIFE

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

Date issued: 05/02/2025

**Available colours & pack sizes:** Please refer to the respective product page on [www.rust-oleum.eu](http://www.rust-oleum.eu) for an overview of actual available colours and pack sizes.

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from [www.rust-oleum.eu](http://www.rust-oleum.eu) or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)