

RUST-OLEUM®
INDUSTRIAL



COATING PRT®

Flexible, long lasting finish for roofs or walls

- Flexible durable paint for renovation of roofs, ideal for making roofs white
- Resistant to UV, acid rain, heat, frost and pollution
- Ideal topcoat for DACFILL® or NOXYDE® to reduce dirt pickup
- Can be used in high humidity areas
- Can also be used on walls

KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

COATING PRT®

DESCRIPTION

Single pack high performance topcoat for walls and roofs, ideal for moist conditions and making roofs white. Also ideal to minimise dirt retention on DACFILL® or NOXYDE®.

ODPORÚČANÉ POUŽITIE

- Coating of inner and outer walls that can be exposed to high humidity, f.i. bathrooms, kitchens, etc.
- Topcoat on Dacfill (improved resistance against stagnating water and less dirt retention) or on Noxyde (less dirt retention)

TECHNICAL DATA

Hustota (g/cm ³):	1,12
Úroveň lesku:	Satin
Obsah pevných látok v hmotnosti:	48%
Obsah pevných látok v objeme:	42%
Testovacie údaje:	SRI value for Coating PRT white after 4000 hours weathering following ISO 16474-3:2020 : 98,2 (requirement: minimum 90)

DRY TIMES BY 20° C/RH 50%

Na dotyk suché:	3 hours
Suché na manipuláciu:	4 hours
Suchý na opätovné natieranie:	24 hours
Úplne vytvrdnuté:	24 hours

ODPORÚČANÁ HRúbKA MOKRÉHO FILMU

140 µm

ODPORÚČANÁ HRúbKA SUCHÉHO FILMU

60 µm

TEORETICKÁ SPOTREBA

7 m²/l

PRAKTICKÁ VÝDATNOSŤ

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application. If the product is applied directly on bitumen felt, the consumption can be considerably higher. Account must be taken of 3.5 m² / l. Apply a test patch before starting the works in order to determine the actual practical consumption.

PRÍPRAVA POVRCHU

Clean the substrate. Allow to dry, any previous coatings must be completely dry.

NÁVOD NA POUŽITIE

To ensure homogeneity, coating materials should be thoroughly stirred prior to use.

PODMIENKY APLIKÁCIE

Work in a dry and well-ventilated area.

APLIKÁCIA A RIEDENIE: ŠTETEC

All types.

APLIKÁCIA A RIEDENIE: VALEC

Short nap-mohair roller.

APLIKÁCIA A RIEDENIE: BEZVZDUCHOVÉ STRIEKANIE

Nozzle: 4/15 - Pressure: 100 bars.

APLIKÁCIA A RIEDENIE: VZDUCHOVO ATOMIZOVANÝ SPREJ

Do not dilute.

ČISTENIE ZARIADENIA / POSTRIEKANIE

Thinner 22 or white spirit.

POZNÁMKY

Reversible paint system, this means that the product dissolves in its own solvent. Can be applied on new concrete.

SAFETY DATA

Úroveň VOC:	481 g/l
VOC readymix:	499 g/l
Kategória VOC:	A/i
Limit VOC:	500 g/l
Grenelle:	Exterior
Poznámky k bezpečnosti:	Consult Safety Data Sheet and Safety Information printed on the can.

SKLADOVATELNOSŤ

Minimum of 5 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

last_updated: 13/05/2025

footer_data_colors_pack_sizes: footer_data_colors_pack_sizes.value

footer_data_disclaimer: footer_data_disclaimer.value

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu