

PROCHEMKO



CURATON CC

Transparent one-component coating for mineral surfaces

- Retains the appearance of the original surface
- Can be painted over quickly
- Water-based formula, ideal for indoor use
- For concrete, natural stone, bluestone, sand-lime brick, etc.
- Suitable as a semi-permanent anti-graffiti coating

WWW.PROCHEMKO.EU

CURATON CC

DESCRIPTION

A transparent, water-based, one-component coating for mineral surfaces, such as concrete, natural stone, bluestone, sand-lime brick, etc.
Retains the 'concrete look', but stops dust and dirt.

RECOMMENDED USE

Curaton CC is suitable for various mineral surfaces, such as concrete, natural stone, bluestone, sand-lime brick, etc.

TECHNICAL DATA

Density (g/cm³): 1,05 kg/l
Gloss Level: Satin
Solids content in volume: 40%

DRY TIMES BY 20° C/RH 50%

Touch dry: 45 min
Dry to recoat: 1-2 hours
Fully cured: 2 days

PRACTICAL CONSUMPTION

Depends on many factors, such as the porosity and roughness of the surface, application method, and material loss when applying the paint.

DIRECTIONS FOR USE

- Dilute and thoroughly mix with maximally 20% water.
- Apply Curaton CC with a brush, roller, or airless spray gun. (15 bar, nozzle opening maximally 0.009 inch)
- Apply at least 3 coats crosswise on the slightly damp (but not wet!) surface. **REMOVING GRAFFITI**
- Apply Rodex around the surface to be cleaned.
- Apply Removex Green or Topper on the surface to be cleaned and allow it enough time to sufficiently soak in.
- Brush or spray off with water at an appropriately high pressure.
- Now treat the surface with diluted Rodex with water (1:10)
- Reapply Curaton CC.

APPLICATION CONDITIONS

Minimum ambient temperature : 5 °C
Maximum relative humidity : 90%
Minimum surface temperature : 5 °C*
Maximum surface temperature: 35 °C
* The surface temperature must be at least 3 °C above the dew point.

CLEANING OF EQUIPMENT / SPILLS

Rinse with clean water immediately after use, but with Graftex 4 if dried out.

REMARKS

Dispose of remnants of the product and empty packaging as chemical waste in accordance with the local regulations and legal requirements.

PH

9,50

SHELF LIFE

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

Date issued: 05/02/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu