



**ON THE JOB
SINCE 1865.**



DryDex®

DryDex Multi-purpose filler, patented Dry Time Indicator

- Dry time indicator - Goes on pink dries white
- No spot priming required
- Won't shrink or crack
- Fills holes up to 10 mm deep
- Versatile all purpose filler for walls & ceilings

WWW.DAP-EUROPE.COM

DESCRIPTION

DAP® DryDex is a premium multi-purpose wall filler formulated with a unique dry time colour indicator that signals when the product is dry & ready to be sanded & painted, eliminating the guesswork of when to finish. Its creamy, ready-to-use formula spreads smoothly and sands easily providing a smooth surface for invisible repairs. This versatile wall filler provides a durable, long-lasting repair that won't sag or crack.

DAP® DryDex is a latex polymer filler.

RECOMMENDED USE

Ideal for multi-purpose interior & exterior repairs to wood, plaster, plasterboard, stone, brick, concrete, primed nail heads.

TECHNICAL DATA

Density (g/cm³): 1,878
Solids Content in weight: 77%

SURFACE PREPARATION

Surface must be clean (free from dirt, dust, grease, debris), dry & structurally sound. Do not apply when temperatures are below 10°C. Do not apply outside if rain is expected within 24 hours. For exterior applications, always overcoat with a high quality exterior-grade paint prior to water exposure. Do not use as a skim coat, on floors, as a sealant, or as a joint filler over cracks & joints where expansion & contraction may occur.

DIRECTIONS FOR USE

- Do not apply when temperatures are below 10°C.
- Do not apply outside if rain is expected within 24 hours.
- Do not use on floors or as a caulk, sealant or joint filler over cracks and joints where expansion and contraction may occur.
- DO NOT USE AS A SKIM COAT.
- For exterior applications, always topcoat with a good quality exterior grade paint.
- If a textured finish is desired, add clean sand to spackling compound prior to application.
- Do not use for tuck pointing applications on brick
- For larger areas to be patched on bare concrete, use a latex fortified Portland cement-based dry mix.

APPLICATION CONDITIONS

1. Surface must be clean, dry and free of foreign material.
2. Stir thoroughly before use. (When using the 5.5 oz squeeze tube, knead tube prior to use. Remove cap and cut nozzle to desired opening size.)
3. Apply with a clean putty knife.
4. One application is usually sufficient for small repairs. For repairs deeper than 1/8", apply two or more layers allowing spackling to dry between applications.
5. For a smoother finish, dip putty knife in water and lightly smooth spackling.
6. Spackling will change color to white when surface can accept a second application or is ready to be painted or sanded in 1 to 5 hours. Wet sanding is recommended to avoid generation of dust.
7. Clean tools immediately with water.

NOTE: To retain the effectiveness of the dry time indicator, keep the container tightly closed after use.

APPLICATION & THINNING: RAKE/TROWEL

1. Stir thoroughly before use.
2. Apply with a clean filling knife, pressing filler firmly into hole.
3. Smooth over filler with a wet or dry filling knife prior to product drying.
4. One application is usually sufficient for shallow repairs. For repairs deeper than 3mm, apply 2 or more layers, allowing filler to dry between applications.
5. Filler will change colour from pink to white when surface can accept a second application or is ready to be sanded or painted (typically 1-5 hours, depending on temperature, humidity

& depth of fill). Paintable with water or oil-based paints. Avoid the inhalation of dust & wear a suitable face mask when sanding.

NOTE: To retain the effectiveness of the dry time indicator, keep the container tightly closed after use

CLEANING OF EQUIPMENT / SPILLS

Clean tools immediately with a cloth & water before product dries. Dried material must be cut or scraped away.

REMARKS

Ensure lid is tightly closed to prevent product from drying out. Be sure container lid/cap is closed and tightly sealed and store in a cool, dry place.

SHELF LIFE

12 months from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5 and 35°C.

Date issued: 23/03/2022

Available colours & pack sizes: Please refer to the respective product page on www.dap-europe.com for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.dap-europe.com or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu