

RUST-OLEUM®
— INDUSTRIAL —



EPOXYSHIELD® CLEANER/DEGREASER



A concentrated cleaner and degreaser for floors.

- Removes grease, oil and other contaminations
- Virtually odour free
- Non-flammable
- 6-8 m²/l coverage

KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

EPOXYSHIELD® CLEANER/DEGREASER

DESCRIPTION

Cleaner/Degreaser for floors is a concentrated, alkaline, non-flammable, virtually odour-free cleaning/degreasing solution.

RECOMMENDED USE

RUST-OLEUM® 2901 - EPOXYSHIELD® Cleaner/Degreaser for floors should be used to remove grease, oil, proteins, dirt and many other surface contaminants from coated, mineral and steel substrates. RUST-OLEUM® 2901 - EPOXYSHIELD® Cleaner/Degreaser for floors should be applied with an artificial sponge, cloth or stiff nylon brush or broom. RUST-OLEUM® 2901 - EPOXYSHIELD® Cleaner/Degreaser for floors can also be used as an additive for high-pressure (steam) cleaning.

THEORETICAL CONSUMPTION

6 - 8 m²/l

PRACTICAL CONSUMPTION

Practical usage depends on many factors such as type and amount of contaminants, shape of the substrate and material losses during application.

DIRECTIONS FOR USE

To ensure homogeneity shake well before use. Scrape or sweep away grease, oil, dirt, mould and all other surface contaminations as much as possible. RUST-OLEUM® 2901 - EPOXYSHIELD® Cleaner/Degreaser for floors can be applied with a sponge, cloth, brush, and broom or cleaning machine. When used in combination with a cleaning machine dilute with 50% cold water. After use rinse with plenty of fresh water. After cleaning, remove any remaining water and allow the surface to dry, as moisture left on the surface or entrapped into pores may cause premature failure of the coating system. Large surface areas or poor drying conditions may require longer drying times before a coating system can be applied.

APPLICATION CONDITIONS

Temperature of air, substrate and material between 5 and 35°C.

REMARKS

Always rinse the surface after cleaning.

SAFETY DATA

VOC level:	9 g/l
Remarks regarding safety:	Consult Safety Data Sheet and Safety Information printed on the can.

SHELF LIFE

Minimum of 2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Date issued: 20/03/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu