



Quality Paints since 1845  
**MATHYS**<sup>®</sup>



## FAIR-DECOR

---

# Additive to prolong the drying time

- To prolong the drying time of waterborne paints

# FAIR-DECOR

## DESCRIPTION

Additive to prolong the drying time of waterborne paints to decorate interior walls in different color effects by sponge, chamois.

## RECOMMENDED USE

Decoration of indoor walls in different colour effects.

## TECHNICAL DATA

Density (g/cm<sup>3</sup>): 1,0  
Solids Content in weight: ± 6 %  
Solids content in volume: ± 6 %

## DRY TIMES BY 20° C/RH 50%

Touch dry: Not applicable  
Dry to handle: Not applicable  
Dry to recoat: After minimum 24 hours (mixture base paint / Fair-Décor)  
Fully cured: Not applicable

## THEORETICAL CONSUMPTION

5 - 15 m<sup>2</sup>/l, depending on the proportion base paint: Fair-Decor

## PRACTICAL CONSUMPTION

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

## SURFACE PREPARATION

After the normal preparations, apply the mixture of Fair-Decor / base paint by roller or flat brush on the substrate which contrasts with the colour of the base paint.

## APPLICATION CONDITIONS

Apply at a temperature of min. 5°C.

## REMARKS

Mix Fair-Decor with a waterborne base paint in the proportion Fair-Decor / base paint 1 : 1 to 1,5 : 1. The finished product has to be considered as a "decorative effect coating" - VOC cat. A1; EU Limit values 300 g/l (2007); 200 g/l (2010).

Treat the wet coat with one of the following techniques: structural roller, sponge, chamois leather, comb, absorbing paper, plastic foil, etc.

Dependent on the paint and the proportion with which Fair-Decor is mixed, it may be advisable to increase the mechanical resistance by applying a final coat of Divalo varnish and this after full cure of the applied mixture.

## SAFETY DATA

VOC limit: 291 g/l  
Remarks regarding safety: Consult safety Data Sheet and Safety Information printed on the can.

## SHELF LIFE

Minimum of 2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Date issued: 07/02/2025

**Available colours & pack sizes:** Please refer to the respective product page on [www.rust-oleum.eu](http://www.rust-oleum.eu) for an overview of actual available colours and pack sizes.

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from [www.rust-oleum.eu](http://www.rust-oleum.eu) or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
info@rust-oleum.eu

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
info@rust-oleum.eu

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
info@rust-oleum.eu

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
info@rust-oleum.eu