

RUST-OLEUM®
— INDUSTRIAL —



9740 FAST BALCONY SYSTEM TOPCOAT

Sealercoat based on a polyaspartic resin system



- Low odour formula
- Walkable after 60-90 mins
- 1-2 coat fully reinforced waterproofing membrane
- Easy to apply and detail
- Low textured, slip resistant finish

KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

9740 FAST BALCONY SYSTEM TOPCOAT

DESCRIPTION

A low solvent odour, flexible top coat for use within the Rust-Oleum Fast Balcony System to encapsulate anti-slip aggregates and provide a durable, full gloss finish

RECOMMENDED USE

The topcoat of the Fast Balcony System system is specifically intended for use on medium to high wear areas on communal balconies and walkways.

RECOMMENDED SYSTEM

Fast Balcony System Grit Coat in combination with Dacfill Fleece
Aluminum Oxide Grits
Fast Balcony System Top Coat

TECHNICAL DATA

Density (g/cm ³):	1,1
Gloss level at 60°:	Gloss
Gloss level at 85°:	Gloss
Solids content in volume:	85%
Mixing Ratio:	Stir base to even consistency then add one complete unit of activator. Mix well to uniform blend, ensuring base material is worked away from sides and bottom of container.

DRY TIMES BY 20° C/RH 50%

Touch dry:	1 hour
Dry to handle:	1,5 hour
Dry to recoat:	min 1,5 hr, max 3 days
Pot Life:	15 minutes at 20°C

RECOMMENDED WET FILM THICKNESS

170 microns

THEORETICAL CONSUMPTION

4-5m²/liter achieves 170-210 microns dr

PRACTICAL CONSUMPTION

Typically 4-6m²/liter. Coverage rate may vary depending on size, type and spreading rate of aluminum oxide grits.

SURFACE PREPARATION

Apply the aggregate in the wet paint film

DIRECTIONS FOR USE

Temperatures above 25°C and very high humidity will reduce pot life. Application at very low temperatures will significantly retard cure. Do not apply when rain is imminent.

APPLICATION & THINNING: BRUSH

Do not thin

APPLICATION & THINNING: ROLLER

Apply one coat by roller to give an even spread, ensuring good cover on entire surface. Apply mixed material as soon as possible to maintain workability. Do not thin.

CLEANING OF EQUIPMENT / SPILLS

Thinner 150

REMARKS

Do not apply to inadequately prepared or unsound surfaces. This product should only be applied by Rust-Oleum approved contractors (further details on request). Substrates must be dry during application otherwise curing defects will occur.

SAFETY DATA

VOC level:	<200 g/l
VOC category:	cat A/j
VOC limit:	500 g/l

SHELF LIFE

12 months from date of production in unopened cans. If stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5°C and 35°C.

Date issued: 16/01/2024

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu