

PROCHEMKO



GECLEAN I HEAVY

Extremely concentrated façade cleaner

- Very quick and effective cleaner
- Cleans all forms of grime - when nothing else works
- Suitable for surfaces not sensitive to acids
- Highly concentrated: dilute maximally to a ratio of 1: 5

GECLEAN I HEAVY

DESCRIPTION

A powerful façade cleaner based on hydrogen fluoride (HF) for removing all kinds of grime when no other product works.

RECOMMENDED USE

This façade cleaner removes stubborn dirt from on all mineral building materials, such as concrete, concrete bricks, masonry and mineral-bound plasters.

DIRECTIONS FOR USE

Dilute Geclean I Heavy with water in the ratio of 1:5.

Use self-adhesive foil to cover surfaces that you do not want to treat, such as paintwork and glass.

Likewise, cover vegetation, paving, and similar next to façades.

Saturate the surface to be treated with water.

Apply Geclean I Heavy with a soft brush, work from the bottom to the top to prevent streaking and spots.

Allow Geclean I Heavy to soak in for 15 to 30 minutes and spray off with a high-pressure hot-water cleaner at a water pressure of at least 80 bar.

Work evenly and carefully to achieve optimum results.

Geclean I Heavy is not suitable for use on acid-sensitive, lime-based surfaces, such as marble and travertine.

Geclean I Heavy damages glass!

APPLICATION CONDITIONS

Minimum ambient temperature : 5 °C

Maximum relative humidity : 100%

Minimum surface temperature : 5 °C

Maximum surface temperature: 30 °C

CLEANING OF EQUIPMENT / SPILLS

Rinse with water immediately after use.

REMARKS

Dispose of remnants of the product, waste water, and empty packaging as chemical waste in accordance with the local regulations and legal requirements.

Hazard

- Fatal when swallowed and in contact with the skin
- Poisonous when inhaled.
- Causes serious burns and eye injuries

Prevention

- Thoroughly wash your hands after working with this product.
- Only use outdoors or in a well-ventilated space.
- Do not eat, drink, or smoke when using this product.
- Wear protective gloves and face protection.
- Wear an apron or overalls when there is a chance of spatters.
- Goggles, face protection, or other full-face protection when there is a chance of direct exposure to aerosols or spatters.

Reaction

AFTER INHALING:

- Bring the person out into fresh air and ensure that can breathe easily.
- Immediately consult a doctor.

AFTER SWALLOWING:

- Rinse the mouth.
- Do not induce vomiting.

CONTACT WITH THE SKIN (or hair):

- Immediately remove contaminated clothing.
- Rinse off the skin with water or take a shower.

CONTACT WITH THE EYES:

- Carefully rinse with water for several minutes.
- If possible, remove contact lenses.
- Continue to rinse.

Storage

- In a well-ventilated location.
- Store in properly closed packaging.
- Keep locked up.
- Dispose of the content and container in accordance with local, regional, national, and international regulations.

SHelf LIFE

Minimum of 24 months. Store in a cool, dry and frost-free environment in the original unopened packaging.

Date issued: 05/02/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu