



GLASTEX

Effectively removes etch streaks from glass

- Very quick and effective cleaning
- Result is crystal-clear
- Dilute maximally to a ratio of 1: 5
- Also suitable as an all-purpose cleaner for surfaces contaminated with metal dust

GLASTEX

DESCRIPTION

Glastex is a highly-powerful concentrated-acid cleaning agent for glass that removes etch streaks from lime or cement.

RECOMMENDED USE

Removes etch streaks on glass on which lime or cement is present.
Do not apply the product if the glass surface to be treated has an acid-sensitive, solar control coating layer, such as a metal oxide.
Suitable as an all-purpose cleaner for surfaces contaminated with metal dust.

PRACTICAL CONSUMPTION

Consumption is greatly dependent on the amount of dirt, dilution, and type of surface.

DIRECTIONS FOR USE

- Dilute Glastex with water maximally to a ratio of 1:5.
- Prevent spatters and drips.
- Clean the surface with a sponge that is wet, but not saturated, with the product.
- Do not let it dry out!
- Afterwards, rinse immediately with a lot of water.

APPLICATION CONDITIONS

Minimum ambient temperature : 10 °C
Maximum relative humidity : 100%
Minimum surface temperature : 10 °C
Maximum surface temperature: 30 °C

REMARKS

Remnants of this product should be treated as chemical waste and may not be disposed of together with business maintenance waste.

Treat empty packaging as industrial waste unless cleaned; otherwise in accordance with the Environmental Management Act and as chemical waste.

pH 1: 15 when diluted with water: 1.7

Damages lime-based surfaces, aluminium, zinc, and certain paint types

Hazard

- Fatal when swallowed and in contact with the skin
- Poisonous when inhaled.
- Causes serious burns and eye injuries

Prevention

- Thoroughly wash your hands after working with this product.
- Only use outdoors or in a well-ventilated space.
- Do not eat, drink, or smoke when using this product.
- Wear protective gloves and face protection.
- Wear an apron or overalls when there is a chance of spatters.
- Goggles, face protection, or other full-face protection when there is a chance of direct exposure to aerosols or spatters.

Reaction

AFTER INHALING:

- Bring the person out into fresh air and ensure that can breathe easily.
- Immediately consult a doctor.

AFTER SWALLOWING:

- Rinse the mouth.
- Do not induce vomiting.

CONTACT WITH THE SKIN (or hair):

- Immediately remove contaminated clothing.
- Rinse off the skin with water or take a shower.

CONTACT WITH THE EYES:

- Carefully rinse with water for several minutes.
- If possible, remove contact lenses.
- Continue to rinse.

Storage

- In a well-ventilated location.
- Store in properly closed packaging.
- Keep locked up.
- Dispose of the content and container in accordance with local, regional, national, and international regulations.

PH

1

SHELF LIFE

Can be kept for a minimum of 12 months from the date of delivery when stored in a dry environment at a temperature between 0 °C and 30 °C in the unopened original packaging.

Date issued: 05/02/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu