



GRAFECO 2

Fresh-smelling ready-to-use graffiti remover

- Quick removal of graffiti
- Fresh smell
- Handy pump spray
- Solvent free
- Suitable for surfaces coated with anti-graffiti coatings

WWW.PROCHEMKO.EU

GRAFECO 2

DESCRIPTION

A fresh, user-friendly, solvent-free graffiti remover with a quick absorption time.

RECOMMENDED USE

This is a graffiti remover for various types of graffiti, such as marker ink, aerosol paints, and similar, on virtually all surfaces. Usable both indoors and outdoors on wood, bare metals, glass, alkyd lacquer, plastic, marble, polyurethane varnish, and Trespa. Safe for most paintwork. Test on the graffiti and surface beforehand!

rest on the graniti and surface before

DIRECTIONS FOR USE

Apply Grafeco 2 to the surface to be treated using a brush or sponge. Allow Grafeco 2 some time to soak in until the graffiti has dissolved. You can use a white non-woven nylon pad as an aid when cleaning. Use a lot of water to rinse off the dissolved graffiti. If necessary, repeat the treatment. To prevent the dissolved graffiti setting on an undesired place, treat the surrounding area of the surface to be treated with Rodex diluted with water to a ratio of 1:10.

APPLICATION CONDITIONS

Minimum ambient temperature : 0 °C Maximum relative humidity : 100% Minimum surface temperature : 0°C Maximum surface temperature: 35 °C

CLEANING OF EQUIPMENT / SPILLS

Rinse with water immediately after use.

REMARKS

Dispose of remaining product, empty packaging, and graffiti remnants as chemical waste in accordance with the local regulations and legal requirements.

PH

8,50

SHELF LIFE

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the unopened original packaging.

Date issued: 05/02/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.

Zilverenberg 16 5234 GM 's-Hertogenbosch The Netherlands T : +31 (0) 165 593 636 F : +31 (0) 165 593 600 info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial) Shadon Way, Portobello Ind. Estate Birtley, Chester-Ie-Street DH3 2RE United Kingdom T : +44 (0)1914 113 146 F : +44 (0)1914 113 147 Info@rust-Ioum au

 Rust-Oleum France S.A.S.

 38, av. du Gros Chêne

 95322 Herblay

 France

 T : +33(0) 130 40 00 44

 F : +33(0) 130 40 99 80

 info@rust-oleum.eu

N.V. Martin Mathys S.A. Kolenbergstraat 23 3545 Zelem Belgium

T : +32 (0) 13 460 200 F : +32 (0) 13 460 201 info@rust-oleum.eu