



GRAFITEX 3

Graffiti remover for plexiglas and plastic

- Does not damage plastics and does not streak
- Ideal for plexiglas and polycarbonate sheeting
- Removes graffiti from bus stops and station signs

WWW.PROCHEMKO.EU

GRAFITEX 3

DESCRIPTION

A graffiti remover for ink and aerosol paint graffiti on non-porous surfaces, such as plexiglas, polycarbonate sheeting, and plastic without streaks.

RECOMMENDED USE

Grafitex 3 is suitable for removing ink and aerosol graffiti on non-porous surfaces. It is also suitable for removing graffiti from anti-graffiti coatings.

DIRECTIONS FOR USE

- Apply Rodex around the surface to be cleaned.
- Use Grafitex 3 as supplied.
- Apply the product using a cloth, sponge, or brush.
- Remove the affected layers using a cloth or grain-free paper.
- If necessary, repeat the treatment.
- Afterwards, treat the surface with Rodex diluted with water (1:10).

APPLICATION CONDITIONS

Minimum ambient temperature : 5 °C Maximum relative humidity : 100% Minimum surface temperature : 5 °C Maximum surface temperature: 35 °C

REMARKS

Dispose of remnants of the product and empty packaging as chemical waste in accordance with the local regulations and legal requirements.

SHELF LIFE

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

Date issued: 05/02/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification

Rust-Oleum Netherlands B.V.

Zilverenberg 16 5234 GM 's-Hertogenbosch The Netherlands T : +31 (0) 165 593 636 F : +31 (0) 165 593 600 info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Ind Shadon Way, Portobello Ind. Estate Birtley, Chester-le-Street DH3 2RE United Kingdom m Industrial) T : +44 (0)1914 113 146 +44 (0)1914 113 147 info@rust-oleum.eu

Rust-Oleum France S.A.S. 38, av. du Gros Chêne 95322 Herblay France T : +33(0) 130 40 00 44 F : +33(0) 130 40 99 80 info@rust-oleum.eu

N.V. Martin Mathys S.A. Kolenbergstraat 23 3545 Zelem Belgium

T : +32 (0) 13 460 200 F: +32(0) 13 460 201 info@rust-oleum.eu