

**RUST-OLEUM®**  
INDUSTRIAL



## NR.1 PAINT STRIPPER

# Highly effective paint and glue remover



- Far more effective than other paint strippers on the market
- Gel like paste works better than liquid alternatives
- Apply as low as 0°C
- Also effective as glue remover
- Quick results

KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

# NR.1 PAINT STRIPPER

## DESCRIPTION

Highly effective paint remover for all paint types and glue without methylene chloride.

## ODPORÚČANÉ POUŽITIE

Nr. 1 Paint Stripper can be used for a quick removal of layers of old paint and glue. Paint Stripper is developed to remove all types of oil- and alkyd based paints, emulsion paints, varnish and most two-component materials from metal, mineral and wooden surfaces. Does not contain methylene chloride, NMP, acids, alkali's, biocides and conservation additives. It will not affect metal, mineral or wooden substrates.

## TECHNICAL DATA

Hustota (g/cm<sup>3</sup>): 0,99  
Pohonná hmota: Dimetyléter

## PRAKTICKÁ VÝDATNOSŤ

Practical coverage depends on many factors such as type of old coating and shape of the substrate and material losses during application.

## PRÍPRAVA POVRCHU

Remove loose coatings as much as possible by scraping.

## NÁVOD NA POUŽITIE

Can: To release possible pressure open the can carefully.  
Aerosol: Remove cover cap. Shake vigorously before use.

## PODMIENKY APLIKÁCIE

Temperature of air, substrate and material between 0 and 30°C and relative humidity below 85%.

## APLIKÁCIA A RIEDENIE: ŠTETEC

Apply Nr. 1 Paint Stripper thickly in an even layer with a brush (disposable brush, flat or round). Do not use synthetic brushes. Allow to stand for 10 to 15 minutes, and remove the old layer with a filling knife or paint scraper. Thick layers of some (two-component) products may need an additional treatment. After use, clean the surface with a cleaner (f.e. ND 14), high pressure (steam) cleaning, fresh water and allow to dry completely before applying a coating.

## APLIKÁCIA A RIEDENIE: AEROSÓL

Hold the can approx. 10-20 cm from the substrate. Apply a uniform foam layer of Paint Stripper 2925; allow standing for minimal 15 minutes, and removing the old layer with a filling knife or paint scraper. Thick layers of some (two-component) products may need an additional treatment. After use, clean the surface with cleaner/degreaser, fresh water or white spirit and allow drying completely before applying a coating.

## POZNÁMKY

Nr. 1 Paint Stripper may affect plastic materials like e.g. PVC, polystyrene. In case of doubt, try on a small test patch beforehand.

## SAFETY DATA

Úroveň VOC: 900 g/l  
Poznámky k bezpečnosti: Do not use in the immediate vicinity of flames, hot surfaces or welding works. No smoking. Consult Safety Data Sheet and Safety Information printed on the can. For the 2.5L & 0.75L: Attention! Open the can carefully to release possible pressure.

## SKLADOVATELNOSŤ

Minimum of 1 year (can) and Minimum of 2 years (aerosol) from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5 and 30°C.

last\_updated: 13/05/2025

footer\_data\_colors\_pack\_sizes: footer\_data\_colors\_pack\_sizes.value

footer\_data\_disclaimer: footer\_data\_disclaimer.value

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
info@rust-oleum.eu

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
info@rust-oleum.eu

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
info@rust-oleum.eu

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
info@rust-oleum.eu