

RUST-OLEUM®
— INDUSTRIAL —



2925 NR.1 PAINT STRIPPER

Highly effective paint and glue remover



- Far more effective than other paint strippers on the market
- Gel like paste works better than liquid alternatives
- Apply as low as 0°C
- Also effective as glue remover
- Quick results

KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

2925 NR.1 PAINT STRIPPER

DESCRIPTION

Highly effective paint remover for all paint types and glue without methylene chloride.

ODPORÚČANÉ POUŽITIE

Nr. 1 Paint Stripper can be used for a quick removal of layers of old paint and glue. Paint Stripper is developed to remove all types of oil- and alkyd based paints, emulsion paints, varnish and most two-component materials from metal, mineral and wooden surfaces. Does not contain methylene chloride, NMP, acids, alkali's, biocides and conservation additives. It will not affect metal, mineral or wooden substrates.

TECHNICAL DATA

Hustota (g/cm³): 0,99
Pohonná hmota: Dimetyléter

PRAKTICKÁ VÝDATNOSŤ

Practical coverage depends on many factors such as type of old coating and shape of the substrate and material losses during application.

PRÍPRAVA POVRCHU

Remove loose coatings as much as possible by scraping.

NÁVOD NA POUŽITIE

Can: To release possible pressure open the can carefully.
Aerosol: Remove cover cap. Shake vigorously before use.

PODMIENKY APLIKÁCIE

Temperature of air, substrate and material between 0 and 30°C and relative humidity below 85%.

APLIKÁCIA A RIEDENIE: ŠTETEC

Apply Nr. 1 Paint Stripper thickly in an even layer with a brush (disposable brush, flat or round). Do not use synthetic brushes. Allow to stand for 10 to 15 minutes, and remove the old layer with a filling knife or paint scraper. Thick layers of some (two-component) products may need an additional treatment. After use, clean the surface with a cleaner (f.e. ND 14), high pressure (steam) cleaning, fresh water and allow to dry completely before applying a coating.

APLIKÁCIA A RIEDENIE: AEROSÓL

Hold the can approx. 10-20 cm from the substrate. Apply a uniform foam layer of Paint Stripper 2925; allow standing for minimal 15 minutes, and removing the old layer with a filling knife or paint scraper. Thick layers of some (two-component) products may need an additional treatment. After use, clean the surface with cleaner/degreaser, fresh water or white spirit and allow drying completely before applying a coating.

POZNÁMKY

Nr. 1 Paint Stripper may affect plastic materials like e.g. PVC, polystyrene. In case of doubt, try on a small test patch beforehand.

SAFETY DATA

Úroveň VOC: 900 g/l
Poznámky k bezpečnosti: Do not use in the immediate vicinity of flames, hot surfaces or welding works. No smoking. Consult Safety Data Sheet and Safety Information printed on the can. For the 2.5L & 0.75L: Attention! Open the can carefully to release possible pressure.

SKLADOVATEĽNOSŤ

Minimum of 1 year (can) and Minimum of 2 years (aerosol) from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5 and 30°C.

last_updated: 20/03/2025

footer_data_colors_pack_sizes: footer_data_colors_pack_sizes.value

footer_data_disclaimer: footer_data_disclaimer.value

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chiène
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu