

RUST-OLEUM®
INDUSTRIAL



GROUND MARKER XL RAL

Spotmarking aerosols in RAL traffic colours.

- Optimised for ground marking
- Extra large can for more linear metres
- Two finger nozzle for accurate writing
- Quick drying (5 - 10 minutes)

KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

GROUND MARKER XL RAL

DESCRIPTION

For quick and easy marking of construction and excavation sites, underground utilities and for traffic safety. Optimised for ground marking. By means of the 360° valve the aerosol is sprayable in all directions. RUST-OLEUM® Spot Marking Aerosol is based on a fast drying acrylic resin. All products in this range are aromatic free and based on lead- and chromate free pigments.

RECOMMENDED USE

RUST-OLEUM® Ground Marker XL Ral can be used on metal, concrete, asphalt, gravel, soil and grass, etc.

RUST-OLEUM® Ground Marker XL Ral: outdoor exposures, normal humidity and interior applications.

RUST-OLEUM® Ground Marker XL Ral is designed for quick and easy marking of construction and excavation sites, underground utilities and for traffic safety.

DRY TIMES BY 20° C/RH 50%

Touch dry:	20 minutes
Dry to recoat:	within 1 hour or after 48 hours
Fully cured:	7 days

THEORETICAL CONSUMPTION

750 ml / 2,25 m² per spray can at 25 µm dry (depending on colour)

PRACTICAL CONSUMPTION

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

SURFACE PREPARATION

Remove dirt, grease, oil and all other surface contaminants by appropriate means. The surface must be clean and dry during application.

DIRECTIONS FOR USE

Remove cover cap. Shake vigorously for at least one minute after the rattle of mixing ball is heard. Shake frequently during use.

It is not possible to clean the spray button in the usual way. Due to the use of the 360° valve this is not necessary.

APPLICATION CONDITIONS

For good results the relative humidity shall be below 85% and the temperature of the can and substrate above 0°C.

SAFETY DATA

VOC level:	637 - 654 g/l
Remarks regarding safety:	Consult Safety Data Sheet and Safety Information printed on the can.

SHELF LIFE

Minimum of 3 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Date issued: 31/03/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu