RUST-OLEUM®
INDUSTRIAL

GRAFFITISHIELD™ CLEANER

Quick and effective removal of graffiti

- Effective in minutes
- Mild aroma
- Universally effective
- Suitable for use in closed spaces
- Removes most paint types

KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

GRAFFITISHIELD™ CLEANER

DESCRIPTION
A specially formulated cleaner for removing graffiti from surfaces pretreated with GraffitiShield™ HYDRO and POLYCOAT.

RECOMMENDED USE
To be used on surfaces which have been treated with GraffitiShield™ HYDRO or POLYCOAT. Also suitable for use on wood, untreated metals, glass, aged alkyd enamels, plastic, polyurethane enamel, Trespa, Plexiglas, and Lexan.

DIRECTIONS FOR USE
Using a brush or sponge, apply GraffitiShield™ Cleaner to the surface to be treated. Allow to soak for several minutes, depending on the temperature, the surface, and the type of graffiti. Once the graffiti has dissolved, it can be removed with a cloth or sponge. Rinse the surface afterwards with plenty of water. Always test on a small area before proceeding to use.

REMARKS
This cleaner is not suitable for use in combination with Martin Mathys Pegagraff Hydro.

PH
4,50

SHELF LIFE
Minimum of 1 year from production date, provided it is stored in the unopened original packaging, in a dry, well-ventilated space, away from direct sunlight, at a temperature between 0° and 30°C.

Date issued: 20/03/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu