

**RUST-OLEUM®**  
— INDUSTRIAL —



## GRAFFITISHIELD™ HYDRO

# Water-based anti-graffiti coating

- Ideal for natural stone types
- Almost invisible result
- No film building
- Excellent UV-resistance
- Transparent protection

KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

# GRAFFITISHIELD™ HYDRO

## DESCRIPTION

Water based permanent anti-graffiti coating with hydrophobic properties for mineral substrates.

## RECOMMENDED USE

GraffitiShield™ HYDRO can be applied to all porous mineral surfaces, such as concrete, brickwork, and dimension stone.

## TECHNICAL DATA

Density (g/cm<sup>3</sup>): 1,0  
Gloss Level: Matt  
Solids content in volume: 10%

## DRY TIMES BY 20° C/RH 50%

Touch dry: 1 hour  
Dry to handle: 1 hour  
Dry to recoat: 1 hour (with itself)  
Fully cured: 3 days

## THEORETICAL CONSUMPTION

5 - 10 m<sup>2</sup>/l

## PRACTICAL CONSUMPTION

Dependent on many factors, such as porosity and roughness of the substrate and material losses during application.

## SURFACE PREPARATION

The surface should be clean, dry, and free of dirt and grease.

## DIRECTIONS FOR USE

Before use, shake up and stir well to ensure a good degree of homogeneity. Lay on two coats, with a drying interval of at least 60 minutes between coats.

## APPLICATION & THINNING: AIRLESS SPRAY

Do not dilute. Nozzle 013-015. It is advisable to cover up windows and doors during application.

## APPLICATION & THINNING: AIR-ATOMISED SPRAY

Do not dilute. It is advisable to cover up windows and doors during application.

## CLEANING OF EQUIPMENT / SPILLS

Water.

## REMARKS

Remove graffiti with GraffitiShield™ CLEANER. GraffitiShield™ HYDRO will remain fully intact once graffiti has been removed, allowing for many rounds of cleaning.

## SAFETY DATA

VOC level: 51 g/l  
VOC readymix: 51 g/l  
VOC category: A/i  
VOC limit: 140 g/l  
Remarks regarding safety: Consult the relevant product safety sheet and information on the packaging.

## SHELF LIFE

Minimum of 1 year from production date, provided it is stored in the unopened original packaging, in a dry, well-ventilated space, away from direct sunlight, at a temperature between 0° and 30°C.

Date issued: 09/12/2025

**Available colours & pack sizes:** Please refer to the respective product page on [www.rust-oleum.eu](http://www.rust-oleum.eu) for an overview of actual available colours and pack sizes.

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from [www.rust-oleum.eu](http://www.rust-oleum.eu) or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)