

RUST-OLEUM®
INDUSTRIAL



GRAFFITISHIELD™ POLYCOAT

Single pack polyurethane anti-graffiti coating

- Hard, smooth surface makes it easy to clean any graffiti on it
- Solvent-free, low odour
- Single pack, non-yellowing polyurethane
- Transparent protection
- Also useful as a colourless varnish for floors

KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

GRAFFITISHIELD™ POLYCOAT

BESKRIVELSE

Single pack solvent-free anti-graffiti protection for many indoor and outdoor substrates.

ANBEFALET BRUG

GraffitiShield™ POLYCOAT is a durable protectant which is suitable for both indoors and out, and for non-absorbent and/or solvent-sensitive surfaces: façade insulation systems, layers of plaster or concrete, but also surfaces which have been treated with acrylic-dispersion paints. This product is not suitable for use on very porous and/or very textured surfaces.

Apply in 1 thin coat (not more than 100µm).

TEKNISK DATA

Tæthed:	1,23
Glansgrad:	Mat
Faststofindhold i vægt:	99%
Tørstofindhold i volumen:	99%

TØRRETIDER VED 20°C/50% RELATIV LUFTFUGTIGHED

Berøringstør:	1 hour
Håndteringstør:	4 hours
Genbehandlingstør:	12 hours
Fuldt hærdet:	3 days
Brugstid:	30 minutes

ANBEFALET VÅDFILM TYKKELSE

100 µm

ANBEFALET TØRFILM TYKKELSE

99 µm

TEORETISK FORBRUG

10 m²/l

PRAKTISK FORBRUG

Dependent on many factors, such as porosity and roughness of the substrate and material losses during application

FORBEHANDLING AF OVERFLADEN

The surface should be clean, dry, and free of dirt and grease.

BRUGSANVISNING

Before use, stir well to ensure a good degree of homogeneity.

ANVENDELSESBETINGELSER

Minimum ambient temperature: 10°C. Maximum relative humidity: 80%. Surface temperature: 5°C-35°C. The temperature of the surface must be at least 3°C higher than the dew point.

PÅFØRING OG FORTYNDING: PENSEL

Do not dilute. Use long-haired brushes made of Chinese pig hair.

PÅFØRING OG FORTYNDING: RULLE

Do not dilute. Use a short-hair roller.

PÅFØRING OG FORTYNDING: LUFTLØS SPRØJTE

Do not dilute.

PÅFØRING OG FORTYNDING: LUFTATOMISERET SPRØJTE

Do not dilute

RENGØRING AF UDSKYR/SPILD

Thinner 160.

BEMÆRKNINGER

Remove graffiti with GraffitiShield™ CLEANER. GraffitiShield™ POLYCOAT will remain fully intact once graffiti has been removed, allowing for several (approx. 5-10) rounds of cleaning. Once the packaging has been opened, the product remains effective for approx. 30 minutes. Leaving the product for longer before applying could be detrimental to the product's sheen.

This product does contain isocyanates. Users must follow mandatory training to comply with EU 2020/1149 Restriction 74.

SIKKERHEDSDATA

VOC-niveau:	10 g/l
VOC-færdigblanding:	10 g/l
VOC-kategori:	A/i
VOC-grænse:	500 g/l
Bemærkninger om sikkerhed:	Consult the relevant product safety sheet and information on the packaging.

HOLDBARHED

Minimum of 1 year from production date, provided it is stored in the unopened original packaging, in a dry, well-ventilated space, away from direct sunlight, at a temperature between 0° and 30°C.

Udstedelsesdato: 10/03/2025

Tilgængelige farver og pakningsstørrelser: Der henvises til den respektive produktside på www.rust-oleum.eu for en oversigt over aktuelle tilgængelige farver og pakningsstørrelser.

Ansvarsfraskrivelse: Oplysningerne heri er efter vores bedste overbevisning korrekte, og er afgivet i god tro, men uden garanti. Brugeren vil blive anset for at selvstændigt at have bekræftet egnetheden af vores produkter til hans/hendes egen særlige formål. Rust-Oleum Europa kan under ingen omstændigheder holdes ansvarlig for følgeskader eller hændelige skader. Produkterne skal opbevares, håndteres og anvendes under forhold, der er i overensstemmelse med Rust-Oleum Europas anbefalinger beskrevet i den nyeste udgave af databladet. Det er brugernes ansvar at sikre, at de har den opdaterede udgave. De nyeste udgaver af datablade kan downloades gratis fra www.rust-oleum.eu eller tilsendes på anmodning til vores kundeservice. Rust-Oleum Europe forbeholder sig ret til at ændre egenskaberne for sine produkter uden forudgående varsel.

Rust-Oleum Netherlands B.V.

Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T: +31 (0) 165 593 636
F: +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)

Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T: +44 (0)1914 113 146
F: +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.

38, av. du Gros Chêne
95322 Herblay
France
T: +33(0) 130 40 00 44
F: +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.

Kolenbergstraat 23
3545 Zelem
Belgium
T: +32 (0) 13 460 200
F: +32 (0) 13 460 201
info@rust-oleum.eu