

RUST-OLEUM®
INDUSTRIAL



GRAFFITISHIELD™ WAX

Anti-graffiti coating based on bee wax

- Virtually invisible sacrificial coating for many surface types
- Biodegradable
- Resistant against UV and weathering
- Low solvent content
- Water vapour permeable

KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

GRAFFITISHIELD™ WAX

DESCRIPTION

Sacrificial layer based on natural wax. Suitable for a single cleaning process.

DOPORUČENÉ POUŽITÍ

Once it has hardened, GraffitiShield™ WAX is very resistant to many types of ink and paint. Graffiti can be easily removed with hot water. Once the graffiti has been removed, the cleaned areas should once again be coated with GraffitiShield™ WAX. Once the hardening period has passed, this will ensure that the treated surface is once again resistant to graffiti. Suitable surfaces: dimension stone, brick, calcium silicate, concrete, acrylic, and marble. It is important that the surfaces used can be cleaned under high pressures, at a water temperature of 70-90°C.

TECHNICAL_DATA

Hustota (g/cm³): 1,02
Úroveň lesku: Satin

DRY TIMES BY 20° C/RH 50%

Dotykem suché: 1 hour
Suché na manipulaci: 12 hours
Suchý nátěr: 2 hours
Plně vytvrzené: 24 hours

TEORETICKÁ SPOTŘEBA

6,7 m²/l

PRAKTICKÁ SPOTŘEBA

Dependent on many factors, such as porosity and roughness of the surface and material losses during application (see DIN 53220).

PŘÍPRAVA POVRCHU

The surface should be clean, dry, and free of dirt and grease.

NÁVOD K POUŽITÍ

Before use, shake up and stir well to ensure a good degree of homogeneity.

PODMÍNKY POUŽITÍ

The working temperature range is between 5°C and 35°C.

APLIKACE A ŘEDĚNÍ: BEZVZDUCHOVÝ SPREJ

Do not dilute. Lay on crosswise in two coats, wet-on-wet, with a break of 10 minutes to 2 hours between the coats. It is advisable to cover up windows and doors during application.

APLIKACE A ŘEDĚNÍ: VZDUCHOVÝ ATOMIZOVANÝ SPREJ

Do not dilute. Lay on crosswise in two coats, wet-on-wet, with a break of 10 minutes to 2 hours between the coats. It is advisable to cover up windows and doors during application.

ČIŠTĚNÍ ZAŘÍZENÍ / ROZLITÍ

Warm water.

POZNÁMKY

Graffiti can be easily removed with a high-pressure cleaner and hot water. When spraying at pressures of 40 bar and upwards, and a minimum temperature of 70-90°C, GraffitiShield™ Wax will melt, removing the graffiti from the surface along with it. After removal, a new layer of GraffitiShield™ Wax should be applied.

SAFETY DATA

Úroveň těkavých organických látek: 25 g/l
VOC readymix: 25 g/l
Kategorie VOC: A/c
Limitní hodnota VOC: 40 g/l
Poznámky k bezpečnosti: Consult the relevant product safety sheet and information on the packaging.

DOBA POUŽITELNOSTI

Minimum of 1 year from production date, provided it is stored in the unopened original packaging, in a dry, well-ventilated space, away from direct sunlight, at a temperature between 0° and 30°C.

last_updated: 13/05/2025

footer_data_colors_pack_sizes: footer_data_colors_pack_sizes.value

footer_data_disclaimer: footer_data_disclaimer.value

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T: +31 (0) 165 593 636
F: +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T: +44 (0)1914 113 146
F: +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T: +33(0) 130 40 00 44
F: +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T: +32 (0) 13 460 200
F: +32 (0) 13 460 201
info@rust-oleum.eu