

RUST-OLEUM®
INDUSTRIAL



GRAFFITISHIELD™ WAX

Anti-graffiti coating based on bee wax



- Virtually invisible sacrificial coating for many surface types
- Biodegradable
- Resistant against UV and weathering
- Low solvent content
- Water vapour permeable

KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

GRAFFITISHIELD™ WAX

DESCRIPTION

Sacrificial layer based on natural wax. Suitable for a single cleaning process.

ODPORÚČANÉ POUŽITIE

Once it has hardened, GraffitiShield™ WAX is very resistant to many types of ink and paint. Graffiti can be easily removed with hot water. Once the graffiti has been removed, the cleaned areas should once again be coated with GraffitiShield™ WAX. Once the hardening period has passed, this will ensure that the treated surface is once again resistant to graffiti. Suitable surfaces: dimension stone, brick, calcium silicate, concrete, acrylic, and marble. It is important that the surfaces used can be cleaned under high pressures, at a water temperature of 70-90°C.

TECHNICAL DATA

Hustota (g/cm³):	1,02
Úroveň lesku:	Satin

DRY TIMES BY 20° C/RH 50%

Na dotyk suché:	1 hour
Suché na manipuláciu:	12 hours
Suchý na opäťovné natieranie:	2 hours
Úplne vytvrdené:	24 hours

TEORETICKÁ SPOTREBA

6,7 m²/l

PRAKTICKÁ VÝDATNOSŤ

Dependent on many factors, such as porosity and roughness of the surface and material losses during application (see DIN 53220).

PRÍPRAVA POVRCHU

The surface should be clean, dry, and free of dirt and grease.

NÁVOD NA POUŽITIE

Before use, shake up and stir well to ensure a good degree of homogeneity.

PODMIENKY APLIKÁCIE

The working temperature range is between 5°C and 35°C.

APLIKÁCIA A RIEDENIE: BEVZDUCHOVÉ STRIEKANIE

Do not dilute. Lay on crosswise in two coats, wet-on-wet, with a break of 10 minutes to 2 hours between the coats. It is advisable to cover up windows and doors during application.

APLIKÁCIA A RIEDENIE: VZDUCHOVO ATOMIZOVANÝ SPREJ

Do not dilute. Lay on crosswise in two coats, wet-on-wet, with a break of 10 minutes to 2 hours between the coats. It is advisable to cover up windows and doors during application.

ČISTENIE ZARIADENIA / POSTRIEKANIE

Warm water.

POZNÁMKY

Graffiti can be easily removed with a high-pressure cleaner and hot water. When spraying at pressures of 40 bar and upwards, and a minimum temperature of 70-90°C, GraffitiShield™ Wax will melt, removing the graffiti from the surface along with it. After removal, a new layer of GraffitiShield™ Wax should be applied.

last_updated: 20/03/2025

SAFETY DATA

Úroveň VOC:	25 g/l
VOC readymix:	25 g/l
Kategória VOC:	A/c
Limit VOC:	40 g/l
Poznámky k bezpečnosti:	Consult the relevant product safety sheet and information on the packaging.

SKLADOVATELNOSŤ

Minimum of 1 year from production date, provided it is stored in the unopened original packaging, in a dry, well-ventilated space, away from direct sunlight, at a temperature between 0° and 30°C.