



KURALTEX VB 311

Cleaning-degreasing agent for heavy grime

- Effective removal of atmospheric fouling
- Also removes degraded paint parts
- Concentrated formula, dilute maximally to a ratio of 1: 20
- Economical to use
- For frames, plastic, floors, etc.

KURALTEX VB 311

DESCRIPTION

A concentrated alkaline cleaner based on surfactants, cleaning enhancers, and lye for heavy fouled plastic and coated surfaces.

RECOMMENDED USE

Kuraltex VB 311 is suitable for cleaning and pre-treating coated surfaces and plastic surfaces before finishing them with, for example, Kuraltex LP 312, Kuraltex BL 314, or NanoSign wax systems.

PRACTICAL CONSUMPTION

Consumption depends heavily on the level of dirt.

DIRECTIONS FOR USE

- Dilute Kuraltex VB 311 maximally to a ratio of 1: 20 depending on the degree of fouling
- Apply the product using a sponge or white pad and allow to soak in for a few minutes.
- Do not allow the product to dry out.
- Rinse off with clean water.
- If needed, use a car-washing brush or pad as an aid.

APPLICATION CONDITIONS

Minimum ambient temperature : 5 °C

Maximum relative humidity : 100%

Minimum surface temperature : 5 °C

Maximum surface temperature: 35 °C

CLEANING OF EQUIPMENT / SPILLS

Rinse with clean water immediately after use.

REMARKS

Dispose of remnants of the product and empty packaging as chemical waste in accordance with the local regulations and legal requirements.

PH

13,10

SHELF LIFE

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

Date issued: 05/02/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu