

**RUST-OLEUM®**  
INDUSTRIAL



## Multi Marker 360°

**For marking & locating in  
construction & civil  
engineering**

- Optimised for ground marking
- Spray through cap for ease of use
- Easier writing
- Quick drying (5 - 10 minutes)

KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

# Multi Marker 360°

## BESKRIVELSE

For quick and easy marking of construction and excavation sites, underground utilities and for traffic safety. Optimised for ground marking. By means of the 360° valve the aerosol is sprayable in all directions. RUST-OLEUM® Spot Marking Aerosol is based on a fast drying acrylic resin. All products in this range are aromatic free and based on lead- and chromate free pigments.

## ANBEFALET BRUG

RUST-OLEUM® Spot Marking Aerosol 2800 can be used on metal, concrete, asphalt, gravel, soil and grass, etc. RUST-OLEUM® Spot Marking Aerosol 2800 is not water-soluble and should be used in light industrial exposures, normal humidity and interior applications. RUST-OLEUM® Spot Marking Aerosol 2800 is designed for quick and easy marking of construction and excavation sites, underground utilities and for traffic safety

## TEKNISK DATA

Glansgrad: Mat  
Varmebestandighed: 100°C (dry heat)

## TØRRETIDER VED 20°C/50% RELATIV LUFTFUGTIGHED

Berøringstør: 5 minutes  
Håndteringstør: 30 minutes

## TEORETISK FORBRUG

500 ml: 1,5 m<sup>2</sup> per spray can at 25 µm dry

## PRAKTISK FORBRUG

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

## FORBEHANDLING AF OVERFLADEN

Remove dirt, grease, oil and all other surface contaminants by appropriate means. The surface must be clean and dry during application.

## ANVENDELSESBETINGELSER

For good results the relative humidity shall be below 85% and the temperature of the can and substrate above 0°C.

## PÅFØRING OG FORTYNDING: AEROSOL

Shake vigorously for at least one minute after the rattle of mixing ball is heard. Shake frequently during use. It is not possible to clean the spray button in the usual way. Due to the use of the 360° valve this is not necessary.

## HOLDBARHED

Minimum of 3 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Udstedelsesdato: 20/05/2025

**Tilgængelige farver og pakningsstørrelser:** Der henvises til den respektive produktside på [www.rust-oleum.eu](http://www.rust-oleum.eu) for en oversigt over aktuelle tilgængelige farver og pakningsstørrelser.

**Ansvarsfraskrivelse:** Oplysningerne heri er efter vores bedste overbevisning korrekte, og er afgivet i god tro, men uden garanti. Brugeren vil blive anset for at selvstændigt at have bekræftet egnetheden af vores produkter til hans/hendes egen særlige formål. Rust-Oleum Europa kan under ingen omstændigheder holdes ansvarlig for følgeskader eller hændelige skader. Produkterne skal opbevares, håndteres og anvendes under forhold, der er i overensstemmelse med Rust-Oleum Europes anbefalinger beskrevet i den nyeste udgave af databladet. Det er brugernes ansvar at sikre, at de har den opdaterede udgave. De nyeste udgaver af datablade kan downloades gratis fra [www.rust-oleum.eu](http://www.rust-oleum.eu) eller tilsendes på anmodning til vores kundeservice. Rust-Oleum Europe forbeholder sig ret til at ændre egenskaberne for sine produkter uden forudgående varsel.

### Rust-Oleum Netherlands B.V.

Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T: +31 (0) 165 593 636  
F: +31 (0) 165 593 600  
info@rust-oleum.eu

### Tor Coatings Ltd (Rust-Oleum Industrial)

Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T: +44 (0)1914 113 146  
F: +44 (0)1914 113 147  
info@rust-oleum.eu

### Rust-Oleum France S.A.S.

38, av. du Gros Chêne  
95322 Herblay  
France  
T: +33(0) 130 40 00 44  
F: +33(0) 130 40 99 80  
info@rust-oleum.eu

### N.V. Martin Mathys S.A.

Kolenbergstraat 23  
3545 Zelem  
Belgium  
T: +32 (0) 13 460 200  
F: +32 (0) 13 460 201  
info@rust-oleum.eu