



MURODEX ZR

Effective facade cleaning paste

- Effective removal of atmospheric, road and urban dirt
- Ideal for brick, cobbles, washed aggregate concrete and yellow brick
- Paste-like gel remains in long contact with the surface for effective cleaning
- Easy to use

MURODEX ZR

DESCRIPTION

Powerful, paste-like, mildly acidic façade cleaner based on inorganic acids, surfactants and thickening agents.

RECOMMENDED USE

Murodex ZR is suitable for cleaning surfaces made of brick, cobblestone, washed aggregate concrete, yellow brick etc.

THEORETICAL CONSUMPTION

Approx 1 - 4 m²/l

PRACTICAL CONSUMPTION

Consumption depends heavily on the level of dirt and type of surface.

SURFACE PREPARATION

Cover plants in the vicinity. Protect all parts not receiving treatment. (Provide good cover for enamelled, painted or varnished surfaces as well as wood, metal and glass)

DIRECTIONS FOR USE

- Apply Murodex ZR using a wide brush or hand brush
- Use the product as supplied
- Allow the product to work for between 3 and 30 minutes
- In the case of heavy dirt use a hard brush beforehand to tackle the surface on which Murodex ZR is to be used
- Spray off with water under the appropriate pressure

APPLICATION CONDITIONS

Minimum ambient temperature: 5°C

Maximum relative humidity: 100%

Minimum surface temperature: 5°C

Maximum surface temperature: 35°C

CLEANING OF EQUIPMENT / SPILLS

Rinse with clean water directly after use.

REMARKS

Dispose of remaining product and empty packaging as chemical waste, in accordance with the local regulations and legal requirements.

PH

4,80

SHELF LIFE

Minimum of 12 months when stored in a dry, cool and frost-free environment in the original, unopened packaging.

Date issued: 05/02/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu