



NANOSIGN® COATEX I

1K Anti-graffiti coating for non-porous surfaces

- one-layer system
- Extremely resistant to solvents
- Extremely durable
- Very simple graffiti remover
- Economical in price

NANOSIGN® COATEX I

DESCRIPTION

A one-component anti-graffiti coating based on nanotechnology (titanium oxide) and high-quality polymers.
Specially developed for non-porous surfaces.

RECOMMENDED USE

NanoSign Coatex is a durable anti-graffiti coating system for the most common non-porous surfaces, such as plastic, paint systems, metals, film, etc.
Some ingredients, such as plasticisers and similar, may change the colour of the surface.
When in doubt, always try out a test surface and let it age for a reasonable period of time.

REMOVING GRAFFITI

- Apply Rodex around the surface to be cleaned.
- Apply Topper on the surface with graffiti to be removed.
- Brush or spray off with water at an appropriately high pressure.
- Now treat the surface with diluted Rodex with water (1:10).

TECHNICAL DATA

Density (g/cm ³):	0,82 kg/l
Gloss Level:	Satin
Solids Content in weight:	15%

PRACTICAL CONSUMPTION

The practical efficiency is dependent on the surface and the application method.

DIRECTIONS FOR USE

Apply Pegalink primer (made to colour) on old paint layers or similar surfaces and finish with a layer of NanoSign-Coatex I.
Clean the surface using NanoSign Pre-Cleaner.
Apply NanoSign Coatex I to a dry, clean, grease-free, dirt-free surface in a single layer.
Apply the product using a microfibre squeegee, brush, spray gun, or short-haired roller.
Apply as a very thin closed layer.

APPLICATION CONDITIONS

Minimum ambient temperature : 5 °C
Maximum relative humidity : 100%
Minimum surface temperature : 5 °C
Maximum surface temperature: 35 °C

CLEANING OF EQUIPMENT / SPILLS

Rinse with Isopropyl Alcohol immediately after use

REMARKS

Product remnants and the empty containers must be disposed of as chemical waste in compliance with local regulations and laws.

SHELF LIFE

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

Date issued: 05/02/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu