



NANOSIGN® EASYWAX POLISH

High-quality polish & protective agent

- Original colour restored
- Polishing and Waxing in one go
- Easy to apply
- Economical solution
- Water and weather resistant

NANOSIGN® EASYWAX POLISH

DESCRIPTION

High-quality polish & protective agent. Especially developed for coated surfaces (mono-colours) with ultra-violet damage (weathering).

RECOMMENDED USE

This is a polishing agent and temporary protection for coated surfaces (mono colours). It is not suitable for profiled surfaces, metallic coatings, or patina layers.

DIRECTIONS FOR USE

CLEAN UP:

Clean the weathered surface with Prochemko Grease Cleaner Foam (1 to 4) using a high-pressure foam pump.

If needed, you can use a white nylon pad as an aid when cleaning up light weathering or wet sand using WP sandpaper 2000 to clean up heavy weathering.

Afterwards, thoroughly wash the surface with water

POLISHES AND WAXES:

Thoroughly shake NanoSign Easy-Wax Polish before use.

Apply with a stiff microfibre or hard-foam pad and polish the surface using an eccentric polisher, such as the Rupes LHR Bigfoot 75E mini (or equivalent) or Bigfoot LHR 21ES/HG (or equivalent).

Note:

1. Apply thinly and evenly
2. Start out at a low RPM and gradually increase the RPMs to achieve the desired effect.
3. Make sure the polishing pad is flush with the surface to prevent excessive heat development.

After polishing and drying using a microfibre cloth, rub until an evenly glossy surface is achieved.

For large areas, test a piece to assess the evenness of the result

APPLICATION CONDITIONS

Minimum ambient temperature : 5 °C

Maximum relative humidity : 100%

Minimum surface temperature: 5 °C

Maximum surface temperature: 35 °C

CLEANING OF EQUIPMENT / SPILLS

Rinse with water immediately after use.

REMARKS

Product remnants and the empty containers must be disposed of as chemical waste in compliance with local regulations and laws.

PH

8

SHELF LIFE

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

Date issued: 05/02/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu