

**RUST-OLEUM®**  
— INDUSTRIAL —

## NS100 ANTI-SLIP

# Anti-slip additive for 1K paints



- Smaller size granules for more subtle anti-slip finish
- Designed for single pack Rust-Oleum® paints
- Can be pre-mixed or broadcasted over wet paint
- HDPE particles distribute very well in wet paint

KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

# NS100 ANTI-SLIP

## DESCRIPTION

Anti-slip HDPE granulate turns a standard floor coating into a durable anti-slip coating.

## RECOMMENDED USE

NS100 Additive is intended to be added to 1K floor paints to produce a subtle non-skid surface, that is not harmful when falling on the floor and easier to clean than coarse anti-slip floors. Ideal for use in bathrooms. Mix with the required RUST-OLEUM paint prior to application.

## TECHNICAL DATA

Density (g/cm<sup>3</sup>): 0,96  
Solids Content in weight: 100%  
Solids content in volume: 100%

## THEORETICAL CONSUMPTION

Use 30g of NS100 per 1L of paint (for example 7200 Floorcoat PU)  
Product comes in a 75g packaging, which is ideal for a 2.5L packaging, for a 5L packaging, use 2 x 75g.

## PRACTICAL CONSUMPTION

Practical usage depends on many factors such as type and amount of contaminants, shape of the substrate and material losses during application.

## DIRECTIONS FOR USE

Mix the granulates into the wet paint material and apply the coating with a roller or a brush (not by spraying), stir regularly to avoid settling of the granulates.

## REMARKS

Particle size: 100 -200 µm.

## SHELF LIFE

5 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Date issued: 07/09/2020

**Available colours & pack sizes:** Please refer to the respective product page on [www.rust-oleum.eu](http://www.rust-oleum.eu) for an overview of actual available colours and pack sizes.

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from [www.rust-oleum.eu](http://www.rust-oleum.eu) or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)