



PARACEM[®] DECO NATURE MATT NF

Matt water-based acrylic paint with Ecolabel

- Optimal coverage, usually in 1 coat
- Easy to use
- Odourless
- Available in any colour
- Ecolabel

PARACEM® DECO NATURE MATT NF

DESCRIPTION

Water-based acrylic paint for high-quality indoor works. Decorative matt coverage for interior walls and ceilings. Applicable on most substrates (plaster, bricks, concrete, etc.) as well in private as in public buildings. With European Ecolabel. The best paint for you and for nature.

RECOMMENDED USE

Decorative and matt finishing for indoor walls and ceilings.
Applicable on most substrates (plaster, bricks, concrete, etc.) in residential and public buildings. Applicable in 2 coats.

TECHNICAL DATA

Density (g/cm ³):	± 1,49
Gloss Level:	Matt
Solids Content in weight:	58 - 62%
Solids content in volume:	41 - 45%
Wet Scrub Resistance (EN 13300):	Class 1 (<5 µm abrasion at 200 strokes)

DRY TIMES BY 20° C/RH 50%

Touch dry:	1 hour
Dry to recoat:	6-8 hours

THEORETICAL CONSUMPTION

8 - 10 m²/l per coat, 2 coats recommended.

PRACTICAL CONSUMPTION

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

SURFACE PREPARATION

The surface should be dry and clean.

DIRECTIONS FOR USE

To ensure homogeneity, coating materials should be thoroughly stirred prior to use.

APPLICATION CONDITIONS

Dry and clean substrates, minimum 10°C

APPLICATION & THINNING: BRUSH

Apply undiluted.

APPLICATION & THINNING: ROLLER

Apply undiluted.

APPLICATION & THINNING: AIRLESS SPRAY

Nozzle: 009 - 011 / Pressure: 200 bars, dilute with maximum 3% volume water.

APPLICATION & THINNING: AIR-ATOMISED SPRAY

If necessary dilute with maximum 3% volume water.

CLEANING OF EQUIPMENT / SPILLS

Water.

REMARKS

When the product is tinted the Ecolabel does not apply anymore. (Adding colorants increases the VOC level).

SAFETY DATA

VOC level:	Max. 9.45 g/l
Remarks regarding safety:	For prolonged or repeated handling, use nitrile rubber gloves. If workers are exposed to concentrations above the exposure limit, they must use respirators. Recommended: organic vapour (Type A) and particulate filter (EN 141). Consult Safety Data Sheet and Safety Information printed on the can.

SHELF LIFE

Minimum of 2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 10° and 35°C.

Date issued: 07/02/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu