

Quality Paints since 1845  
**MATHYS**<sup>®</sup>



## PARACEM<sup>®</sup> DECO NATURE SATIN NF

# Satin water-based acrylic paint with Ecolabel

- Excellent flow
- Excellent mechanical resistance against rubbing
- Smooth satin matt aspect
- Closed coating structure
- High covering power

# PARACEM® DECO NATURE SATIN NF

## DESCRIPTION

Waterborne acrylic paint for high-quality indoor works. Decorative and satin finishing for indoor walls and ceilings. Applicable on most substrates (plaster, bricks, concrete, etc.) as well in private as in public buildings. With European Ecolabel. The best paint for you and for nature.

## RECOMMENDED USE

Decorative finishing for indoor walls and ceilings. Applicable on most substrates (plaster, bricks, concrete, etc.) in residential and public buildings.

## TECHNICAL DATA

Density (g/cm <sup>3</sup> ):	1,36
Gloss Level:	Satin
Solids Content in weight:	57 - 61%
Solids content in volume:	42 - 46%
Wet Scrub Resistance (EN 13300):	Class 1 (<5 µm abrasion at 200 strokes)

## DRY TIMES BY 20° C/RH 50%

Touch dry:	1 hour
Dry to recoat:	6-8 hours

## THEORETICAL CONSUMPTION

10 - 12 m<sup>2</sup>/l per coat, 2 coats recommended

## PRACTICAL CONSUMPTION

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application (see DIN 53220).

## SURFACE PREPARATION

Old cleaned layers in good condition and light porous substrates may be coated directly with Paracem Deco Nature. Very porous substrates, smooth plaster and water-resistant plasterboard are to be impregnated first with Paracem Deco Nature Primer.

## DIRECTIONS FOR USE

To ensure homogeneity, coating materials should be thoroughly stirred prior to use.

## APPLICATION CONDITIONS

Dry and clean substrates, minimum 10°C.

## APPLICATION & THINNING: BRUSH

Apply undiluted.

## APPLICATION & THINNING: ROLLER

Apply undiluted.

## APPLICATION & THINNING: AIRLESS SPRAY

Nozzle: 9 - 11 / Pressure: 200 bars, dilute with maximum 3% volume water.

## APPLICATION & THINNING: AIR-ATOMISED SPRAY

If required dilute with maximum 3% volume water.

## CLEANING OF EQUIPMENT / SPILLS

Water.

## REMARKS

When the product is tinted the Ecolabel does not apply anymore.

## SAFETY DATA

VOC level:	Max. 0.5 g/l
Remarks regarding safety:	Consult Safety Data Sheet and Safety Information printed on the can.

## SHELF LIFE

Minimum of 2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Date issued: 07/02/2025

**Available colours & pack sizes:** Please refer to the respective product page on [www.rust-oleum.eu](http://www.rust-oleum.eu) for an overview of actual available colours and pack sizes.

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from [www.rust-oleum.eu](http://www.rust-oleum.eu) or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
info@rust-oleum.eu

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
info@rust-oleum.eu

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
info@rust-oleum.eu

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
info@rust-oleum.eu