



PARACEM[®] EFFECTS SAND-SABLE

Waterborne acrylic paint with fine sand structure

- Long open time (2-3 hours)
- No tendency to overlap
- Splash free
- Good hiding power
- odourless

PARACEM® EFFECTS SAND-SABLE

DESCRIPTION

Waterborne acrylic paint with fine sand structure for application on interior walls.

RECOMMENDED USE

Aesthetical embellishment of most common interior substrates (plaster, bricks, concrete); also applicable on glass fibre.

TECHNICAL DATA

Density (g/cm³): ± 1,3 - 1,4
Solids Content in weight: ± 48%
Solids content in volume: ± 30%

DRY TIMES BY 20° C/RH 50%

Touch dry: 4 hours
Dry to recoat: 24 hours
Fully cured: 1 day

RECOMMENDED WET FILM THICKNESS

90 µm

RECOMMENDED DRY FILM THICKNESS

27 µm

THEORETICAL CONSUMPTION

± 8 m²/kg

PRACTICAL CONSUMPTION

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

SURFACE PREPARATION

Walls in bad condition: Eliminate carefully the old paint or non-adherent plaster; sanding with metallic brush. Large repairs to be performed with cement mixture or Pegacrete. Small repairs to be performed with a mixture of Paracem Quartz and fine sand. After drying, these repairs shall be primed with Pegafix. Seal joints and fissures with Elastofill. Old cleaned paint coats in good condition and slightly porous substrates can be repainted immediately with Paracem Effects Sand / Sable. porous substrates should be primed with Cachemire Sand Primer or, for very fast recoating, with Zinsser primers Bulls Eye 123 or 123 Plus. Block water and nicotine stains with Pegamat RL or Pegamat Aqua Isole, or Zinsser primers Bulls Eye 123, 123 Plus, or B-I-N.

DIRECTIONS FOR USE

To ensure homogeneity, coating materials should be thoroughly stirred prior to use.

APPLICATION CONDITIONS

> 5°C, < 80% R.H.

APPLICATION & THINNING: BRUSH

Apply with Paracem Effects brush in cross movements. If necessary, dilute with water.

CLEANING OF EQUIPMENT / SPILLS

Water.

SAFETY DATA

VOC level: 179 g/l
VOC ready mix: 179 g/l
VOC category: A/i
VOC limit: 200 g/l
Remarks regarding safety: Consult Safety Data Sheet and Safety Information printed on the can.

SHELF LIFE

Minimum of 2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Date issued: 07/02/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu