



Quality Paints since 1845
MATHYS[®]



PEGAPRIM[®] EXTERIOR

Water-based primer

- Reinforces the substrate and reduces absorption
- Neutralises differences in absorption characteristics
- Prevents differences in the glossiness of the topcoat
- Very good hiding characteristics
- Improves topcoat adhesion

PEGAPRIM® EXTERIOR

DESCRIPTION

Water-based primer based on acrylic dispersions. Neutralises differences in the absorption characteristics of the substrate. Provides a substrate with uniform absorption and colour.

RECOMMENDED USE

Acrylate primer for exterior applications. Can be applied to most mineral substrates

TECHNICAL DATA

Density (g/cm ³):	± 1,35 (weiss)
Gloss Level:	Matt
Gloss level at 60°:	Matt: ± 5%
Solids Content in weight:	58 % (weiss)
Solids content in volume:	45 % (weiss)

DRY TIMES BY 20° C/RH 50%

Touch dry:	1,5 hours
Dry to recoat:	2-3 hours
Fully cured:	1 week

RECOMMENDED WET FILM THICKNESS

100 µm

RECOMMENDED DRY FILM THICKNESS

45 µm

THEORETICAL CONSUMPTION

± 8 - 10 m²/l

PRACTICAL CONSUMPTION

Depends on several factors such as porosity and roughness of the substrate and material losses during application (see DIN 53220).

SURFACE PREPARATION

The substrate should be dry, clean and free of grease. Pegaprim Exterior may be directly applied over normally porous substrates and old, cleaned paint layers if they are in good condition. Not suitable for highly porous substrates; use Pegafix as a fixator in such cases.

DIRECTIONS FOR USE

The product should be thoroughly stirred before use, to ensure homogeneity.

APPLICATION CONDITIONS

> 5°C, < 80% R.H.

APPLICATION & THINNING: BRUSH

Use undiluted.

APPLICATION & THINNING: ROLLER

Use undiluted.

APPLICATION & THINNING: AIRLESS SPRAY

Nozzle: 011 - 015 / Pressure: 180 - 200 bar.

Apply undiluted.

APPLICATION & THINNING: AIR-ATOMISED SPRAY

Use undiluted.

CLEANING OF EQUIPMENT / SPILLS

Water.

SAFETY DATA

VOC level:	30 g/l
VOC readymix:	30 g/l
VOC category:	A/g
VOC limit:	30 g/l
Remarks regarding safety:	Refer to the Product Data Sheet and the information on the packaging.

SHELF LIFE

At least 2 years from manufacturing date, if stored in the unopened, original packaging in dry, well-ventilated areas, not in direct sunlight, and at temperatures between 5° and 35°C.

Date issued: 04/07/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu