



**PROCHEMKO**



## **POLITEX**

---

# **Concentrated floor wax for refreshing old linoleum**

- Effective dirt and water repellence
- Restores shine
- Good wear resistance
- Resists UV, does not yellow
- Ideal for old or worn linoleum

# POLITEX

## DESCRIPTION

A concentrated floor wax based on acrylate polymers, special waxes and other additives for rubber, linoleum, unglazed floor tiles, concrete floors, washed gravel tile floors and cork.

## RECOMMENDED USE

Shiny floor wax for synthetic floors such as rubber, linoleum and such like, unglazed floor tiles, concrete floors, coated floors, washed gravel tile floors and cork. (not to be used on Pegulan, Mipolan or wooden floors)

## TECHNICAL DATA

Density (g/cm<sup>3</sup>): 1,02 kg/l  
Solids content in volume: 21%

## DRY TIMES BY 20° C/RH 50%

Touch dry: 30 min  
Dry to handle: 1.5 h

## RECOMMENDED WET FILM THICKNESS

100 µm (undiluted), 80 µm (diluted)

## RECOMMENDED DRY FILM THICKNESS

20 µm (undiluted), 10 µm (diluted)

## THEORETICAL CONSUMPTION

10 m<sup>2</sup>/l. (undiluted)

## PRACTICAL CONSUMPTION

In practice the consumption depends on the roughness of the surface and the desired appearance.

## SURFACE PREPARATION

Dust off the surface and make it clean and dry.

## DIRECTIONS FOR USE

Dilute Politex with water to a maximum of 1 : 2.5 (too much dilution hinders film formation). Apply the product in two layers, crossways, using a soaper. Allow the first layer to dry for at least 6 -8 hours before applying the second layer. To acquire the best possible shine use Politex diluted with water in the ratio 1 : 2.5 and apply with the help of a misting nozzle and a high speed machine. (minimum 2000 t/min)

## APPLICATION CONDITIONS

Minimum ambient temperature: 10°C  
Maximum relative humidity: 90%  
Minimum surface temperature: 10°C  
Maximum surface temperature: 35°C

## CLEANING OF EQUIPMENT / SPILLS

Rinse with clean water directly after use.

## REMARKS

Dispose of remaining product and empty packaging as chemical waste, in accordance with the local regulations and legal requirements.

## PH

8

## SHELF LIFE

Minimum of 12 months when stored in a dry, cool and frost-free environment in the original, unopened packaging.

Date issued: 05/02/2025

**Available colours & pack sizes:** Please refer to the respective product page on [www.rust-oleum.eu](http://www.rust-oleum.eu) for an overview of actual available colours and pack sizes.

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from [www.rust-oleum.eu](http://www.rust-oleum.eu) or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
info@rust-oleum.eu

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
info@rust-oleum.eu

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
info@rust-oleum.eu

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
info@rust-oleum.eu