



Quality Paints since 1845
MATHYS[®]



PORISOL[®]

Pore-filler

- Fixing
- Isolating
- Nearly odorless
- Can be recoated with water dispersed and most synthetic paints

DESCRIPTION

Waterborn impregnating agent.

RECOMMENDED USE

As a pore-filler (inside): undiluted on very porous substrates (cardboard, paper, light kinds of woods), diluted on substrates with different absorption capacity (plaster, wood-fibre boards, etc.)

As a sealer (inside): undiluted on exotic wood, aniline colours and surfaces soiled with coaltar. Do not apply on substrates soiled with fume residues or soot (isolate first with Pegamat)

TECHNICAL DATA

Density (g/cm ³):	1,03 - 1,06
Gloss Level:	Gloss
Solids Content in weight:	50 - 52 %
Solids content in volume:	48 - 50 %

DRY TIMES BY 20° C/RH 50%

Touch dry:	30 minutes
Dry to recoat:	1 hour

RECOMMENDED WET FILM THICKNESS

100 µm

RECOMMENDED DRY FILM THICKNESS

48 µm

THEORETICAL CONSUMPTION

3 - 10 m²/l per coat

PRACTICAL CONSUMPTION

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

SURFACE PREPARATION

The surfaces to be treated must be sound and dry. Remove non adhering parts (by scraping and rubbing), dust off carefully and degrease, if necessary.

APPLICATION & THINNING: BRUSH

If necessary dilute with water.

APPLICATION & THINNING: ROLLER

If necessary dilute with water.

CLEANING OF EQUIPMENT / SPILLS

Water.

REMARKS

When used as an impregnating agent, dilute 1/1 with water on substrates soiled with fume residue or soot, use Pegamat instead of Porisol.

SAFETY DATA

VOC level:	0 g/l
VOC readymix:	0 g/l
VOC category:	A/g
VOC limit:	30 g/l
Remarks regarding safety:	Consult Safety Data Sheet and Safety Information printed on the can.

SHELF LIFE

Minimum of 2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Date issued: 07/02/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu