

RUST-OLEUM®
— INDUSTRIAL —



PRE-PAINT CLEANER



Concentrated pre-paint cleaner for most surfaces

- Multi-surface cleaner for walls, window/door frames, floors and metals
- No further rinsing is needed after wiping the surface; saves time
- Effortlessly removes all organic and inorganic pollution
- Makes the surface anti-static to prevent adhesion of dust prior to painting
- Non-foaming, biodegradable formulation

KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

PRE-PAINT CLEANER

DESCRIPTION

Effective, concentrated biodegradable cleaner to quickly clean all types of surfaces prior to painting.

DOPORUČENÉ POUŽITÍ

Pre-paint Cleaner for all types of surfaces: floors, walls, doors, window frames, metal, windows, door frames, etc. Cleans, degreases and also removes nicotine stains. Makes the surface anti-static to prevent adhesion of dust prior to painting. Does not foam.

TEORETICKÁ SPOTŘEBA

Ca. 100 m²/l at a dilution of 1 : 20

PRAKTICKÁ SPOTŘEBA

Practical coverage depends on many factors such as porosity, roughness of the substrate, contamination level and dilution during application.

NÁVOD K POUŽITÍ

Shake well before use. Scrape off grease, oil, dirt and other pollution as much as possible. Dilute RUST-OLEUM® Pre-paint cleaner to the required mixture and apply on the surface. Rub with a brush or white nylon pad and allow to work in for several minutes if necessary. Then wipe thoroughly with a damp sponge or cloth. With stubborn soiling repeat the treatment or leave to work in longer, possibly with a higher concentration.

PODMÍNKY POUŽITÍ

Temperature of air, substrate and material between 5 and 35°C.

POZNÁMKY

Because of its concentrated composition, Pre-Paint Cleaner is very economical in use. Depending on the degree of contamination, the product should be diluted in a ratio of between 1:10 and 1:100.

- 1 : 10 ovens, motors, extremely dirty floors
- 1 : 20 kitchens, machines, gas stoves, garden furniture
- 1 : 50 paintwork, nicotine stains
- 1 : 100 windows, mirrors, sun-beds etc.

SAFETY DATA

Úroveň těkavých organických látek:	0 g/l
Poznámky k bezpečnosti:	Consult Safety Data Sheet and Safety Information printed on the can.

PH

9

DOBA POUŽITELNOSTI

Minimum of 2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 40°C.

last_updated: 20/03/2025

footer_data_colors_pack_sizes: footer_data_colors_pack_sizes.value

footer_data_disclaimer: footer_data_disclaimer.value

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chiène
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu