

RUST-OLEUM®
INDUSTRIAL



PRE-PAINT CLEANER



Concentrated pre-paint cleaner for most surfaces

- Multi-surface cleaner for walls, window/door frames, floors and metals
- No further rinsing is needed after wiping the surface; saves time
- Effortlessly removes all organic and inorganic pollution
- Makes the surface anti-static to prevent adhesion of dust prior to painting
- Non-foaming, biodegradable formulation

KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

PRE-PAINT CLEANER

BESKRIVELSE

Effective, concentrated biodegradable cleaner to quickly clean all types of surfaces prior to painting.

ANBEFALET BRUG

Pre-paint Cleaner for all types of surfaces: floors, walls, doors, window frames, metal, windows, door frames, etc. Cleans, degreases and also removes nicotine stains. Makes the surface anti-static to prevent adhesion of dust prior to painting. Does not foam.

TEORETISK FORBRUG

Ca. 100 m²/l at a dilution of 1 : 20

PRAKTISK FORBRUG

Practical coverage depends on many factors such as porosity, roughness of the substrate, contamination level and dilution during application.

BRUGSANVISNING

Shake well before use. Scrape off grease, oil, dirt and other pollution as much as possible. Dilute RUST-OLEUM® Pre-paint cleaner to the required mixture and apply on the surface. Rub with a brush or white nylon pad and allow to work in for several minutes if necessary. Then wipe thoroughly with a damp sponge or cloth. With stubborn soiling repeat the treatment or leave to work in longer, possibly with a higher concentration.

ANVENDELSESBETINGELSER

Temperature of air, substrate and material between 5 and 35°C.

BEMÆRKNINGER

Because of its concentrated composition, Pre-Paint Cleaner is very economical in use. Depending on the degree of contamination, the product should be diluted in a ratio of between 1:10 and 1:100.

1 : 10 ovens, motors, extremely dirty floors

1 : 20 kitchens, machines, gas stoves, garden furniture

1 : 50 paintwork, nicotine stains

1 : 100 windows, mirrors, sun-beds etc.

SIKKERHEDSDATA

VOC-niveau: 0 g/l

Bemærkninger om sikkerhed: Consult Safety Data Sheet and Safety Information printed on the can.

PH

9

HOLDBARHED

Minimum of 2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 40°C.

Udstedelsesdato: 20/03/2025

Tilgængelige farver og pakningsstørrelser: Der henvises til den respektive produktseite på www.rust-oleum.eu for en oversigt over aktuelle tilgængelige farver og pakningsstørrelser.

Ansvarsfraskrivelse: Oplysningerne heri er efter vores bedste overbevisning korrekte, og er afgivet i god tro, men uden garanti. Brugeren vil blive ansat for at selvstændigt at have bekræftet egnetheden af vores produkter til hans/hendes egen særlige formål. Rust-Oleum Europa kan under ingen omstændigheder holdes ansvarlig for følgeskader eller hændelige skader. Produkterne skal opbevares, håndteres og anvendes under forhold, der er i overensstemmelse med Rust-Oleum Europes anbefalinger beskrevet i den nyeste udgave af databladet. Det er brugernes ansvar at sikre, at de har den opdaterede udgave. De nyeste udgaver af datablade kan downloades gratis fra www.rust-oleum.eu eller tilsendes på anmodning til vores kundeservice. Rust-Oleum Europe forbeholder sig ret til at ændre egenskaberne for sine produkter uden forudgående varsel.

Rust-Oleum Netherlands B.V.

Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)

Shadon Way, Portobello Ind. Estate
Birley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.

38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.

Kolenbergstraat 23
3545 Zellem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu