

**RUST-OLEUM®**  
INDUSTRIAL



## PRE-PAINT CLEANER



# Concentrated pre-paint cleaner for most surfaces

- Multi-surface cleaner for walls, window/door frames, floors and metals
- No further rinsing is needed after wiping the surface; saves time
- Effortlessly removes all organic and inorganic pollution
- Makes the surface anti-static to prevent adhesion of dust prior to painting
- Non-foaming, biodegradable formulation

KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

# PRE-PAINT CLEANER

## BESKRIVELSE

Effective, concentrated biodegradable cleaner to quickly clean all types of surfaces prior to painting.

## ANBEFALT BRUK

Pre-paint Cleaner for all types of surfaces: floors, walls, doors, window frames, metal, windows, door frames, etc. Cleans, degreases and also removes nicotine stains. Makes the surface anti-static to prevent adhesion of dust prior to painting. Does not foam.

## TEORETISK FORBRUK

Ca. 100 m<sup>2</sup>/l at a dilution of 1 : 20

## PRAKTISK FORBRUK

Practical coverage depends on many factors such as porosity, roughness of the substrate, contamination level and dilution during application.

## BRUKSANVISNING

Shake well before use. Scrape off grease, oil, dirt and other pollution as much as possible. Dilute RUST-OLEUM® Pre-paint cleaner to the required mixture and apply on the surface. Rub with a brush or white nylon pad and allow to work in for several minutes if necessary. Then wipe thoroughly with a damp sponge or cloth. With stubborn soiling repeat the treatment or leave to work in longer, possibly with a higher concentration.

## PÅFØRINGSBETINGELSER

Temperature of air, substrate and material between 5 and 35°C.

## MERKNADER

Because of its concentrated composition, Pre-Paint Cleaner is very economical in use. Depending on the degree of contamination, the product should be diluted in a ratio of between 1:10 and 1:100.

1 : 10 ovens, motors, extremely dirty floors

1 : 20 kitchens, machines, gas stoves, garden furniture

1 : 50 paintwork, nicotine stains

1 : 100 windows, mirrors, sun-beds etc.

## SIKKERHETSDATA

VOC nivå: 0 g/l

Merknader angående sikkerhet: Consult Safety Data Sheet and Safety Information printed on the can.

## PH

9

## HOLDBARHET

Minimum of 2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 40°C.

Utstedt dato: 20/03/2025

**Tilgjengelige farger & størrelse på forpakninger:** Vennligst referer til den respektive produktsiden på [www.rust-oleum.eu](http://www.rust-oleum.eu) for en oversikt over tilgjengelige farger og størrelse på forpakninger.

**Ansvarsfraskrivelse:** Så langt vi kjenner til er informasjonen i dette dokumentet korrekt og nøyaktig. Den er gitt i god tro, men uten garanti. Brukeren må selv avgjøre om våre produkter er egnet for hans/hennes bestemte formål. Ikke under noen omstendigheter skal Rust-Oleum Europe bli gjort ansvarlig for indirekte eller tilfældige skader. Produktene må lagres, håndteres og påføres under forhold som tilfredsstiller Rust-Oleum Europes anbefalinger som er detaljert beskrevet i den siste oppdaterte kopien av produktdatabladet. Brukerne er selv ansvarlige for at de har den siste oppdaterte kopien. De siste oppdaterte kopier av produktdatablad er tilgjengelig, og kan lastes ned gratis fra [www.rust-oleum.eu](http://www.rust-oleum.eu), eller de kan fås ved forespørsel til vår kundeserviceavdeling. Rust-Oleum Europe forbeholder seg retten til å endre egenskapene til produktene sine uten forhåndsvarsel.

### Rust-Oleum Netherlands B.V.

Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
info@rust-oleum.eu

### Tor Coatings Ltd (Rust-Oleum Industrial)

Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
info@rust-oleum.eu

### Rust-Oleum France S.A.S.

38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
info@rust-oleum.eu

### N.V. Martin Mathys S.A.

Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
info@rust-oleum.eu