

PROCHEMKO



R.A.P.P.

Paint and Coating stripper

- Powerful paint stripper
- For almost all surfaces
- Methylene chloride free
- Also available in a handy aerosol

WWW.PROCHEMKO.EU

R.A.P.P.

DESCRIPTION

For the quick and efficient removal of just about all paint types, including two-component epoxy and polyurethane coatings.

For use on just about all surfaces. First perform a test on synthetic surfaces.

RECOMMENDED USE

R.A.P.P. is suitable for removing Alkyd paint, water-based paints, two-component epoxyethane and polyurethane coatings, and one-component polyurethane coatings. For use on almost all surfaces.

With plastic and polyester, always try out a test surface.

PRACTICAL CONSUMPTION

Consumption is highly dependent on the layer thickness of the paint coating and the roughness of the surface.

DIRECTIONS FOR USE

Apply a generous layer of the product on the surface to be treated.

Let the product soak in for at least 30 minutes.

Remove the paint remnants using a scraper, spatula, or, in the event of graffiti, a white pad.

If necessary, repeat the treatment.

When removing multiple paint layers, cover the R.A.P.P. with plastic foil and allow to soak in for a few hours.

Brush or spray off using (warm) water at an appropriately high pressure.

After removing the old paint, clean the treated surface using **Rodex** diluted with water (1:10).

APPLICATION CONDITIONS

Minimum ambient temperature : 0 °C.

Minimum surface temperature: 0 °C

The work will be slower at low temperatures.

CLEANING OF EQUIPMENT / SPILLS

Rinse with water immediately after use, but with thinner if dried out.

REMARKS

Remnants of this product should be treated as chemical waste and may not be disposed of together with commercial or household waste.

SHELF LIFE

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

Date issued: 05/02/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu