

RUST-OLEUM®
INDUSTRIAL



AQUA SATIN



Acrylic-based, gloss top coat

- Quick drying
- Contains a low concentration of solvents
- Virtually odour-free
- Scratch-resistant
- Excellent hiding capacity

KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

AQUA SATIN

DESCRIPTION

Acrylic-based, scratch-resistant, durable, colour-fast satin gloss top coat with excellent hiding power. For interior use.

RECOMMENDED USE

Can be applied to wood, board, primed metal, plastics and plasterwork.

RECOMMENDED SYSTEM

Substrate: Surfaces must be clean, dry and free from dust or grease.

Untreated wood: Degrease, sand lightly and remove any dust. Next, apply Acrylic Primer. Allow to dry. Next sand the surface, remove dust and fill any irregularities if present. Apply primer to filled areas. Finish with 1 or 2 coats of Acrylic Lacquer Silk.

Painted surfaces in good condition: Carefully degrease with a degreasing agent, sand down until matt and remove dust. If necessary, fill irregularities with filler and apply Acrylic Primer to the filler when dry. Sand to a smooth finish. Finally, apply 1 top coat of Acrylic Lacquer Silk.

Painted surfaces in poor condition: Remove all poorly adhering paint using paint stripper or a blowtorch/hot air paint removal gun. Then treat as "Untreated wood".

Untreated MDF, chipboard, etc.: Degrease, sand lightly and remove any dust. Apply Acrylic Primer after diluting with 5 - 10% water. Allow to dry, sand and remove dust. Next, apply a second undiluted coat of Acrylic Primer. Finish with 1 or 2 coats of Acrylic Lacquer Silk.

Untreated metal: Carefully remove grease, any mill scale and rust. Pre-treat with a suitable rust preventive primer. Next, apply an undiluted coat of Acrylic Primer. Finally, apply 1 top coat of Acrylic Lacquer Silk.

Hard plastics: Degrease, lightly sand and remove any dust. Pre-treat with 1 coat of Universal Primer and finish by applying a top coat of Acrylic Lacquer Silk.

TECHNICAL DATA

Density (g/cm ³):	1.2
Gloss Level:	Satin
Gloss level at 60°:	35-50%
Solids content in volume:	35%

DRY TIMES BY 20° C/RH 50%

Touch dry:	1 h
Dry to recoat:	6 h

RECOMMENDED WET FILM THICKNESS

µ

RECOMMENDED DRY FILM THICKNESS

35 µ

THEORETICAL CONSUMPTION

Approx. 14 m²/litre per coat

PRACTICAL CONSUMPTION

Depending on the object to be painted and the application method.

SURFACE PREPARATION

Surfaces must be clean, dry and free from dust or grease.

DIRECTIONS FOR USE

Stir thoroughly prior to use. Apply 1 or 2 coats using an acrylic paint brush, acrylic paint roller or paint sprayer. The first layer can be diluted with up to 3% of water. After every coat, lightly sand down and remove dust.

APPLICATION CONDITIONS

Stir thoroughly prior to use. We recommend applying at temperatures between 8°C and 30°C. After use, close the container correctly and store in an upright position in a frost-free area. Do not close doors and windows until the paint has dried fully (after a minimum of 8 hours).

CLEANING OF EQUIPMENT / SPILLS

Water and soap

SAFETY DATA

VOC readymix:	40 g/l
VOC category:	A/d
VOC limit:	130 g/l
Remarks regarding safety:	Surplus product: This paint and the packaging should be disposed of at a collection point for hazardous or special waste.

SHELF LIFE

Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

Date issued: 20/03/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T: +31 (0) 165 593 636
F: +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T: +44 (0)1914 113 146
F: +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T: +33(0) 130 40 00 44
F: +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T: +32 (0) 13 460 200
F: +32 (0) 13 460 201
info@rust-oleum.eu