

RUST-OLEUM®
INDUSTRIAL



FIX PRIMER



Water-based, colourless fixing agent

- Stabilises powdery surfaces
- Good penetration performance
- Improves finishing coat adhesion
- Improves finishing coat coverage
- Solvent-free and virtually odourless

KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

FIX PRIMER

DESCRIPTION

Water-based, colourless fixing agent based on synthetic resin for substrates with a powdery, porous or highly absorbent surface. Deep penetrative capacity, improves adhesion to the substrate and increases the efficiency of the finishing coat. Solvent-free, low-odour and quick drying. For interior and exterior use.

RECOMMENDED USE

As a primer on powdery and absorbent substrates. Suitable substrates are, for example: cement and plasterwork, concrete, brickwork, plasterboard, board, etc.

RECOMMENDED SYSTEM

General: The surface must have a load-bearing capacity and must be fully set, dry and free from dust or grease. Sand and repair surface irregularities. Remove and/or repair all loose and unstable coats. When using externally, remove all algae and moss.

New, untreated substrates

- Prime absorbent and highly absorbent surfaces in their entirety using Stabilising primer (prevent glossy patches).
- Thoroughly clean powdery surfaces. Prime with Stabilising primer after allowing to dry.

Existing, non-load-bearing substrates

- Thoroughly remove loose coats.
- Thoroughly wash powdery coats and allow to dry.
- Carry out any repairs.
- Prime with Stabilising primer.

The aforementioned systems form a general description of the most common substrates. Please contact Rust-Oleum Europe for specific applications and/or detailed advice.

DRY TIMES BY 20° C/RH 50%

Touch dry: 1 h
Dry to recoat: 4 h

THEORETICAL CONSUMPTION

Approx. 6-10 m²/litre per coat

PRACTICAL CONSUMPTION

Actual consumption depends on the nature and the structure of the surface and the application method.

SURFACE PREPARATION

The surface must have a load-bearing capacity and must be fully set, dry and free from dust or grease. Sand and repair surface irregularities. Remove and/or repair all loose and unstable coats. When using externally, remove all algae and moss.

DIRECTIONS FOR USE

Shake and stir before use. Apply in 1 coat preferably using a square pasting brush or a woolly roller. Never allow this product to form a film.

APPLICATION CONDITIONS

Do not use at temperatures below +8°C. Only use when the surface temperature is at least 3°C above the dew point temperature. Do not apply outdoors when it is likely to rain or when frost is expected. Do not apply outdoors in direct sun. When using this product, always use the necessary personal protective equipment. Always ventilate in a suitable way during use.

CLEANING OF EQUIPMENT / SPILLS

Water and soap

SAFETY DATA

VOC level: 0 g/l
VOC category: A/h
VOC limit: 30 g/l
Remarks regarding safety: Surplus product: This paint and the packaging should be disposed of at a collection point for hazardous or special waste.

SHELF LIFE

Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

Date issued: 20/03/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T: +31 (0) 165 593 636
F: +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T: +44 (0)1914 113 146
F: +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T: +33(0) 130 40 00 44
F: +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T: +32 (0) 13 460 200
F: +32 (0) 13 460 201
info@rust-oleum.eu