

RUST-OLEUM®
— INDUSTRIAL —



GLOSS



High gloss decorative top coat

- High opacity
- Durable gloss retention
- For interior and exterior use

KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

GLOSS

DESCRIPTION

High gloss paint with perfect hiding power. Decorative with excellent weather-resistant properties and long-lasting gloss retention. Durable protection of wood, hard plastics and metal. For interior and exterior use.

RECOMMENDED USE

On wood and pre-treated metal and plastic

RECOMMENDED SYSTEM

Substrate: Surfaces must be clean, dry and free from dust or grease.

Untreated internal wood: Degrease, sand lightly and remove any dust. Next, apply Primer. Allow to dry. Next sand the surface, remove dust and fill any irregularities if present. Apply primer to filled areas. Untreated external wood: Degrease, sand lightly and remove any dust. Next, apply Primer. After drying, sand, make free of dust and fill irregularities if required. Next, apply a second undiluted coat of Primer.

Painted surfaces in good condition: Carefully degrease with a degreasing agent, sand down lightly and remove dust. If necessary, fill irregularities with filler and apply Primer. Sand to a smooth finish. Painted surfaces in poor condition: Remove all poorly adhering paint using paint stripper or a blowtorch/hot air paint removal gun. Then treat as "Untreated wood".

Untreated MDF, chipboard, etc.: Degrease, sand lightly and remove any dust. Next, apply Primer. Allow to dry. Next sand the surface, remove dust and fill any irregularities if present. Next, apply a second coat of Primer. Untreated metal: Carefully remove grease, any mill scale and rust. First treat with a suitable anti-rust minimum. Next, apply a coat of Primer.

Hard plastics: Degrease, lightly sand and remove any dust. Prime with 1 coat of Multi Primer.

Plasterwork: Surfaces must be completely dry and free from dust or grease. Next, apply 1 coat of Primer.

TECHNICAL DATA

Density (g/cm ³):	0.94-1.14
Gloss Level:	Gloss
Gloss level at 60°:	>80%
Solids Content in weight:	70-75%

DRY TIMES BY 20° C/RH 50%

Touch dry:	3 h
Dry to recoat:	20 h

RECOMMENDED WET FILM THICKNESS

70 µ

RECOMMENDED DRY FILM THICKNESS

45 µ

THEORETICAL CONSUMPTION

Approx. 14-16 m²/litre per coat

PRACTICAL CONSUMPTION

Actual consumption depends on the nature and the structure of the surface and the application method.

SURFACE PREPARATION

Surfaces must be clean, dry and free from dust or grease.

DIRECTIONS FOR USE

Stir thoroughly prior to use. Apply with a brush, roller or paint sprayer. Indoors: 1 or 2 thin coats; outdoors: always apply 2 thin coats. After every coat, lightly sand down and remove dust.

IMPORTANT: Respect the efficiency and drying time between coats. Coats that are too thick slow down the drying time and may lead to defects in the dry film.

APPLICATION CONDITIONS

We recommend applying at +8°C and +30°C., indirect sunlight or when rain is expected.

Products based on alkyd resins have a tendency to yellow in a dark environment or when covered. When exposed to daylight, this phenomenon is much reduced.

After use, close the container correctly, turn it around for a few seconds to ensure that skin formation cannot occur and store in an upright position.

CLEANING OF EQUIPMENT / SPILLS

White spirit or paint cleaner

SAFETY DATA

VOC readymix:	300 g/l
VOC category:	A/d
VOC limit:	300 g/l
Remarks regarding safety:	Surplus product: This paint and the packaging should be disposed of at a collection point for hazardous or special waste.

SHELF LIFE

Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

Date issued: 20/03/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the user's responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu