

RUST-OLEUM®
INDUSTRIAL



PREMIUM COVER SOFT

High quality, excellent covering acrylic wall paint



- Optimum flow
- Scrub-resistant, class 1 (DIN EN 13300)
- Highly weather-resistant
- Silk matt
- Excellent hiding power

KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

PREMIUM COVER SOFT

DESCRIPTION

High quality, excellent covering 100% acrylic wall paint with a silk matt finish. Intended for a durable, decorative finish of walls and ceilings. Also suitable for damp rooms and exterior walls. Scrub-resistant(Class 1). For inside and outside.

RECOMMENDED USE

Intended for a durable, decorative finish to walls, ceilings, facades and damp spaces. Due to its superior quality, it is extremely suitable for outdoor work where high demands are placed on it. Suitable substrates are for example: existing wall paint layers, cement and plaster, concrete, brick, etc.

RECOMMENDED SYSTEM

General: The surface must have a load-bearing capacity and must be fully set, dry and free from dust or grease. Sand and repair surface irregularities. Remove and/or repair all loose and unstable coats. When using externally, remove all algae and moss.

New, untreated substrates

- Prime highly absorbent surfaces in their entirety using Stabilising primer.
- Thoroughly clean powdery surfaces. Prime with Stabilising primer after allowing to dry.
- Paint to cover after allowing to dry.

Existing intact coats of wall paint

- Clean using Paint cleaner.
- Apply an intermediate coat of Wall Primer Opaque if required.
- Paint to cover after allowing to dry.

Existing, non-load-bearing coats of wall paint

- Remove loose parts.
- Thoroughly wash powdery coats and allow to dry.
- Carry out any repairs.
- Prime with Stabilising primer.
- Paint to cover after allowing to dry.

Contamination caused by nicotine, damp, rust or soot

- Clean thoroughly.
- Treat surface/contamination using Sealing primer.
- Paint to cover after allowing to dry.

The aforementioned systems form a general description of the most common surfaces. Please contact Rust-Oleum Europe for specific applications and/or detailed advice.

TECHNICAL DATA

Density (g/cm ³):	1.44
Gloss Level:	Semi-Matt
Gloss level at 60°:	10%
Gloss level at 85°:	20-30%
Solids content in volume:	40%

DRY TIMES BY 20° C/RH 50%

Touch dry:	2 h
Dry to recoat:	6 h

RECOMMENDED WET FILM THICKNESS

110 µ

RECOMMENDED DRY FILM THICKNESS

46 µ

THEORETICAL CONSUMPTION

Approx. 9 m²/litre per coat

PRACTICAL CONSUMPTION

Actual consumption depends on the nature and the structure of the surface and the application method.

SURFACE PREPARATION

The surface must have a load-bearing capacity and must be fully set, dry and free from dust or grease. Sand and repair surface irregularities. Remove and/or repair all loose and unstable coats. When using externally, remove all algae and moss.

DIRECTIONS FOR USE

Stir thoroughly prior to use. The first coat can be diluted with a maximum of 10% water. Apply in 1 or 2 coats using a suitable brush, paint roller or paint sprayer. Always work wet-on-wet to prevent visible brush strokes. Retouch all lengths in the same direction. Do not retouch when drying.

APPLICATION CONDITIONS

Do not use at temperatures below +8°C. Only use when the surface temperature is at least 3°C above the dew point temperature. Do not apply outdoors when it is likely to rain or when frost is expected. Do not apply outdoors in direct sun. When using this product, always use the necessary personal protective equipment. Do not inhale the spray or fumes from products. Always ventilate in a suitable way during use.

APPLICATION & THINNING: AIRLESS SPRAY

Nozzle: 0.017-0.019"
Pressure: approx. 180 bars
Dilute: 0-10%

The stated settings for spraying this product form the starting point. Depending on the conditions on site, the person responsible for applying the product must determine the settings.

APPLICATION & THINNING: AIR-ATOMISED SPRAY

Nozzle: 0.017-0.019"
Pressure: approx. 120 bars
Air pressure: approx. 2 bars
Dilute: 0-10%

The stated settings for spraying this product form the starting point. Depending on the conditions on site, the person responsible for applying the product must determine the settings.

CLEANING OF EQUIPMENT / SPILLS

Water

Date issued: 20/03/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu

PREMIUM COVER SOFT

SAFETY DATA

VOC level: 5 g/l
VOC category: A/a
VOC limit: 30 g/l
Remarks regarding safety: Surplus product: This paint and the packaging should be disposed of at a collection point for hazardous or special waste.

SHELF LIFE

Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

Date issued: 20/03/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu