



## STAINLESS STEEL CLEANER FRD

# Powerful stainless-steel cleaner

- Removes heavily corroded and oxidised coatings
- Also removes blue discolouration from welding, anodic coatings, and residues of polishing compounds
- Does not contain abrasives
- Does not contain chloride, hydrochloric acid, or solvents
- Rinses off well with water

# STAINLESS STEEL CLEANER FRD

## DESCRIPTION

A cleaner based on an inorganic acid for cleaning stainless steel (quality 316), chrome, copper, nickel, and aluminium. Also suitable for staining welding areas.

## RECOMMENDED USE

FRD Stainless Steel Cleaner is suitable for cleaning stainless steel (316 grade), chrome, copper, nickel, and aluminium.

It removes heavily corroded and oxidised layers, blue discolouration from welding, anodic layers, and the residues of polishing compounds.

## PRACTICAL CONSUMPTION

Consumption is dependent on the degree of fouling and corrosion.

## DIRECTIONS FOR USE

Use the product as supplied to you.

Apply Stainless Steel Cleaner FRD using a brush, sponge, or poly spray gun, and allow to soak in for 15 to 120 minutes.

Do not use it on hot panels!

Do not let the product dry out!

Thoroughly rinse off with water.

If necessary, use a car brush or white pad as an aid.

First, create a test surface.

Clean using Stainless Steel Cleaner FRD, protect with Kuraltex BL 314 or NanoSign coating systems.

## APPLICATION CONDITIONS

Minimum ambient temperature : 5 °C

Maximum relative humidity : 100%

Minimum surface temperature : 5 °C

Maximum surface temperature: 30 °C

## CLEANING OF EQUIPMENT / SPILLS

Rinse with clean water immediately after use.

## REMARKS

Dispose of remnants of the product and empty packaging as chemical waste in accordance with the local regulations and legal requirements.

## PH

1,40

## SHELF LIFE

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

Date issued: 05/02/2025

**Available colours & pack sizes:** Please refer to the respective product page on [www.rust-oleum.eu](http://www.rust-oleum.eu) for an overview of actual available colours and pack sizes.

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from [www.rust-oleum.eu](http://www.rust-oleum.eu) or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)