

PROCHEMKO



SARDEX

Removes atmospheric dirt

- Removes dirt, efflorescence and soot
- Also removes limescale in showers, toilets; saunas and on tiles
- No effect on healthy metal, rubber, glass and such like
- Concentrated formula, for max. dilution 1 : 20

SARDEX

DESCRIPTION

Strong acidic, low viscosity liquid cleaner based on inhibited inorganic acids; removes atmospheric dirt, rust, salt efflorescence and damage from fire and soot on concrete stone and concrete.

RECOMMENDED USE

Sardex is suitable for removing atmospheric dirt, rust, salt efflorescence and damage from fire and soot from concrete stone and concrete. Also suitable for the removal of limescale in showers, toilets, saunas and on tiles.

THEORETICAL CONSUMPTION

Approx 4 - 8 m²/l

PRACTICAL CONSUMPTION

Consumption depends heavily on the level of dirt, the dilution and type of surface.

DIRECTIONS FOR USE

- Dilute Sardex with water to a maximum of 1 : 20
- Apply Sardex using a brush, cloth or paintbrush
- Allow the product to work for a few minutes
- Rinse off extremely well with water

APPLICATION CONDITIONS

Minimum ambient temperature: 5°C

Maximum relative humidity: 100%

Minimum surface temperature: 5°C

Maximum surface temperature: 35°C

CLEANING OF EQUIPMENT / SPILLS

Rinse with clean water directly after use.

REMARKS

Dispose of remaining product and empty packaging as chemical waste, in accordance with the local regulations and legal requirements.

PH

2

SHELF LIFE

Minimum of 12 months when stored in a dry, cool and frost-free environment in the original, unopened packaging.

Date issued: 05/02/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu