

PROCHEMKO



SARDEX FORTE

Removes lime, rust, soot, and carbon from concrete

- Effective cleaner for surfaces made of concrete and concrete blocks
- Descaler and rust remover
- Extremely fast action
- Also suitable for removing cement residues

WWW.PROCHEMKO.EU

SARDEX FORTE

DESCRIPTION

Description: highly-concentrated, thin liquid, acidic cleaner based on inhibited inorganic acids. Removes lime, rust, soot, and carbon from concentrated. It is also a descaling agent and cement residues remover.

RECOMMENDED USE

Sardex Forte is suitable for removing lime, rust, soot, and carbon from concrete and facing bricks.
Also suitable for descaling pipes, cleaning concrete surfaces damaged by fire and soot, and removal of cement residues and similar.

THEORETICAL CONSUMPTION

Circa 4 - 8 m²/l

PRACTICAL CONSUMPTION

Consumption is greatly dependent on the amount of dirt, dilution, and type of surface.

DIRECTIONS FOR USE

- Wet the surface with water.
- Dilute Sardex Forte with water maximally to a ratio of 1 : 5
- Apply the product using a brush
- Allow the product to soak in for a few minutes
- Afterwards, thoroughly rinse off with water

APPLICATION CONDITIONS

Minimum ambient temperature : 5 °C
Maximum relative humidity : 100%
Minimum surface temperature : 5 °C
Maximum surface temperature: 35 °C

CLEANING OF EQUIPMENT / SPILLS

Rinse with clean water immediately after use.

REMARKS

Dispose of remnants of the product and empty packaging as chemical waste in accordance with the local regulations and legal requirements.
The recommended cleaner by MBI Concrete and others.

SHELF LIFE

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

Date issued: 05/02/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu