

**RUST-OLEUM®**  
— INDUSTRIAL —



## **SUPERGRIP® TREADSAFE**

# **Revêtement pour sols epoxy anti-dérapante.**

- Applicable jusqu'à 0°C
- Finition robuste et durable
- Application une couche
- Utilisation à l'extérieur et à l'intérieur

**LE SAVOIR-FAIRE EN PROTECTION™**

**WWW.RUST-OLEUM.EU**



# SUPERGRIP® TREADSAFE

## DESCRIPTION

Revêtement pour sols epoxy anti-dérapante. 2-Pack revêtement de sol époxy pour le béton et la pierre.

## UTILISATION RECOMMANDÉE

Treadsafe is ideal for use on floors, stairs, ramps, loading bays and boat decks etc. It can be applied on concrete floors, which are completely clean and dry. It is not recommended to apply on smooth/dense concrete or concrete containing a curing compound, which will prevent a good adhesion.

## TEMPS DE SÉCHAGE À 20°C/HR 50%

|                            |                                                                                                                                                                             |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Manipulable:               | 24 hours                                                                                                                                                                    |
| Dur à cœur:                | 7 days                                                                                                                                                                      |
| Pot-life (vie du mélange): | Approximately 30 minutes to 1 hour at a temperature of 20°C when decanted into a shallow tray. Pot life will be reduced if the mixed components are left in the mixing tin. |

## CONSUMMATION THÉORIQUE

Rust-Oleum Treadsafe is supplied in a pack designed to cover 5m². Comprises epoxy resin, hardener and anti-slip aggregate.

## PRÉPARATION DE SURFACE

Surfaces to be treated must be at least four weeks old, completely dry and free of surface laitance (a weak dusty layer on concrete), contaminants and any previous poorly bonded coatings. Very smooth concrete or concrete with surface laitance should be etched with a etchant to ensure adequate adhesion. Other surfaces should be dry and free of all loose surface material, contaminants and rust.

## PRÉCAUTIONS D'UTILISATION

Pour the liquid contents of the two small tins (resin and hardener) into the larger outer tin and mix thoroughly until uniform in colour. Do not mix in the anti-slip aggregate. The mixed components should be decanted into a shallow tray and be used immediately. (If they are not decanted the components and mixing tin will become quite hot and unusable).

## CONDITIONS D'APPLICATION

Store Treadsafe at a temperature range of 15°C - 25°C for 8 hours prior to use. This will ensure easier application of the mixed resin and hardener and maximise pot life.

## APPLICATION & DILUTION: ROULEAU

A pile-type roller (not foam) should be used to apply the mixture from a shallow roller tray over an area of up to 5m². Immediately sprinkle the anti-slip aggregate uniformly over the wet coat to obtain the desired surface finish (total or light coverage). Using the same roller, roll over the sprinkled aggregate to bed it in and cover it with the mixture. It is not normally necessary to re-charge the roller with mixed resin unless very heavy quantities of grit have been applied.

## NETTOYAGE DU MATERIEL / ECLABOUSSURES

It is not practical to clean applicators and they should be discarded after use. White Spirit or similar solvent will remove accidental splashes (if treated immediately).

## REMARQUES

To ensure best performance, DO NOT PAINT IF THE FOLLOWING CONDITIONS EXIST: 1) Sealed concrete: dripping a small amount of water onto the surface. If the water beads, a sealer is present and paint may not adhere properly. 2) Moisture in the concrete: apply a sheet of plastic (e.g. garbage bag) to the floor. Tape down the edges and allow to set for 24 hours. If water droplets appear on the inside of the plastic or if concrete appears wet (darker in color), moisture is trapped in the concrete. 3) Loose concrete or concrete dust: if the concrete is loose, chipping or has concrete dust present, the coating will not perform properly unless all loose material and dust is removed and damaged areas are repaired. 4) Floors treated with a levelling mortar or on anhydride floors.

## DONNÉES DE SÉCURITÉ

|                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Teneur en COV:              | 30 g/l                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| COV prêt à l'emploi:        | 30 g/l                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Catégorie COV:              | A/j                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Remarques pour la sécurité: | Avoid contact with skin and eyes. For skin contact, wash affected area with soap and water and rinse well. First aid: in case of contact with eyes, flush with cold water for 15 minutes. If swallowed, do not induce vomiting. Drink 1-2 glasses of water or milk. Contact a physician immediately. Keep out of reach of children. Do not take internally. Consult for further information the Safety Data Sheet and the Safety Information printed on the can. |

## DURÉE DE VIE

2 ans minimum à partir de la date de production dans l'emballage d'origine non ouvert, à condition d'être stocké dans un local sec, correctement ventilé, à l'abri des rayons du soleil et à des températures entre 5 et 35°C.

Date d'émission: 13/05/2025

**Couleurs et conditionnements disponibles:** Reportez-vous à la page produit concernée sur [www.rust-oleum.eu](http://www.rust-oleum.eu) pour avoir un aperçu des couleurs et des tailles d'emballage actuellement disponibles.

**Notion de responsabilité:** Les informations communiquées ici sont véridiques et exactes et sont fournies de bonne foi au meilleur de nos connaissances, mais sans garantie. Il est estimé que l'utilisateur se sera assuré lui-même de la compatibilité de nos produits avec son usage particulier. Rust-Oleum Europe ne sera en aucun cas tenue pour responsable quant aux dommages consécutifs ou indirects. Les produits doivent être stockés, manipulés et appliqués conformément aux conditions respectant les recommandations de Rust-Oleum Europe détaillées dans le dernier exemplaire de la fiche technique du produit. Il incombe aux utilisateurs de veiller à disposer de l'exemplaire actuel. Les dernières versions de la fiche technique du produit sont disponibles gratuitement et peuvent être téléchargées sur [www.rust-oleum.eu](http://www.rust-oleum.eu) ou sur demande adressée à notre département Service à la clientèle. Rust-Oleum Europe se réserve le droit de modifier les propriétés de ses produits sans avis préalable.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)