

RUST-OLEUM[®]
— INDUSTRIAL —



THINNER 191

Thinner based on aromatic hydrocarbons

- Correct solvent combination for Rust-Oleum polyurethane system 9600
- Strong diluting capacity
- Especially for spray applications

KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

THINNER 191

DESCRIPTION

Solvent with high diluting capacity based on aromatic hydrocarbons, especially suitable for spray application dilution of polyurethane based coatings.

DOPORUČENÉ POUŽITÍ

Thinning solution for spray application of the following products:

- 569 Quick drying metal primer
- 769 Damp-proof rust primer
- 1060/1080 High build metal primer
- 7200 Floorcoat PU
- 7500 Alkythane
- 9600 Rust-o-Thane ®

PODMÍNKY POUŽITÍ

Mix coating thoroughly. Thin only if necessary. Follow the thinning recommendations provided on the individual product label. Excessive thinning and the use of non-recommended thinners can be detrimental to service life and performance of the coating.

POZNÁMKY

See the Product Data sheet of the respective product for further details.

SAFETY DATA

Úroveň těkavých organických

látek: 877 g/l

Poznámky k bezpečnosti:

Safety sheet available for professional user upon request.

DOBA POUŽITELNOSTI

Minimum of 5 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

last_updated: 20/03/2025

footer_data_colors_pack_sizes: footer_data_colors_pack_sizes.value

footer_data_disclaimer: footer_data_disclaimer.value

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chiène
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu